



AGENDA BRUNSWICK COUNTY PLANNING BOARD

***6:00 P.M. Monday
June 11, 2018***

***Commissioners Chambers
David R. Sandifer Administration Bldg.
Brunswick County Government Center***

- 1) Call to Order.
- 2) Invocation.
- 3) Pledge of Allegiance.
- 4) Roll Call.
- 5) Consideration of the Minutes of the May 14, 2018 Meeting.
- 6) Agenda Amendments.
- 7) Public Comment.
- 8) Public Hearings.
 - A. Proposed Unified Development Ordinance Text Amendment Related to Revisions to the Flood Damage Prevention Ordinance.
 - B. Proposed Flood Maps Approved by FEMA.
- 9) Other Business.
 - A. Planning Board Case Update
- 10) Adjournment.

MINUTES
PLANNING BOARD
BRUNSWICK COUNTY, NC

6:00 P.M. Monday
May 14, 2018

Commissioners Chambers
David R. Sandifer Administration Bldg.
County Government Center
Old U.S 17 East

MEMBERS PRESENT

Eric Dunham, Chair
Joy Easley, Vice Chair
Richard Leary
Ron Medlin
Troy Price
Tom Simmons
Randy Ward

MEMBERS ABSENT

None

STAFF PRESENT

Kirstie Dixon, Director
Brandon Hackney, Project Planner
Connie Marlowe, Admin. Asst. II
Marc Pages, Senior Planner
Bryan Batton, Asst. County Attorney

OTHERS PRESENT

Joseph Keech
Tariq Nizam
Lewis Dozier
Marva Ross
Robin Vanvliet

Terry Pope, State Port Pilot
John Hankins
William Bittenbender, Alternate
Edward Vanvliet

I. CALL TO ORDER.

The Chair called the meeting to order at 6:01 p.m.

II. INVOCATION/PLEDGE OF ALLEGIANCE.

Mr. Dunham said a prayer. The Chair asked everyone to stand and face the U.S. Flag to say the Pledge of Allegiance.

III. ROLL CALL.

There were no members absent.

IV. CONSIDERATION OF MINUTES OF THE 09-APR-18 MEETING.

Ms. Easley made a motion to approve the minutes as written and the motion was unanimously carried.

V. AGENDA AMENDMENTS.

Ms. Dixon asked that an Item E (Planning Board Training) be added to Other Business.

VI. PUBLIC COMMENT.

There were none.

VII. PUBLIC HEARINGS.

A. Rezoning Z-763 – Joseph Keech

Request to rezone approximately 2.60 acres located off Mt. Misery Road NE (SR 1426) and Arden Road NE near Leland from R-6000 (High Density Residential to C-LD (Commercial Low Density) for Tax Parcel 023PD005.

Mr. Pages addressed the Board. He read the Staff Report (attached). He identified the subject property and surrounding properties on a visual map and he provided drone footage of the area.

Mr. Pages said staff recommends approval from R-6000 (High Density Residential) to C-LD (Commercial Low Density) for Tax Parcel 023PD005.

Mr. Dunham asked staff about the existing commercial zoning in the area. Mr. Pages said there are some nearby properties that are in the Town of Leland, but the other commercial properties within the County's jurisdiction were originally zoned as such.

Ms. Easley made a motion to open the Public Hearing and the motion was unanimously carried.

Mr. Joseph Keech, property owner, addressed the Board. Mr. Keech said they purchased the subject property in November 2017 and they developed Summerlin Estates which is northwest of the subject property. Mr. Keech said this area, specifically Mt. Misery Road NE (SR 1426), is in transition and the subject property is better suited for commercial purposes.

With no further comments, Mr. Ward made a motion to close the Public Hearing and the motion was unanimously carried.

Mr. Leary made a motion to recommend to the Board of Commissioners to approve Tax Parcel 023PD005 to C-LD and the motion was unanimously carried.

THEREFORE, on the basis of all the foregoing, IT IS ORDERED that the ZONING AMENDMENT be recommended to the Board of Commissioners for

APPROVAL – CONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment is consistent with the CAMA Land Use Plan (Comprehensive Plan) for the following reasons:

The proposed zoning amendment is consistent with the Comprehensive Plan (CAMA Land Use Plan), in that, this area is mixed use.

- The Planning Board further finds that the proposed zoning amendment is reasonable and in the public interest for the following reasons:

The area is in transition as there is existing commercial zoning nearby and there were no objections to the zoning change.

B. Rezoning Z-764 – Tariq Nizam

Request to rezone approximately 1.65 acres located off Stone Chimney Road SW (SR 1119) and Old Ferry Road Connection SW (SR 1115) near Holden Beach from R-7500 (Medium Density Residential) to C-LD (Commercial Low Density) for Tax Parcels 2160007604, 2160007605, 2160007608 and 2160007609.

Land Use Plan Map Amendment LUM-764:

Request to amend Tax Parcels 2160007604, 2160007605, 2160007608 and 2160007609 located off Stone Chimney Road SW (SR 1119) and Old Ferry Connection Road SW (SR 1115) near Holden Beach from LDR (Low Density Residential) to Commercial.

Mr. Pages addressed the Board. He read the Staff Report (attached). He identified the subject property and surrounding properties on a visual map and he provided drone footage of the area.

Mr. Pages said staff recommends approval from R-7500 (Medium Density Residential) to C-LD (Commercial Low Density) for Tax Parcels 2160007604, 2160007605, 2160007608 and 2160007609 in conjunction with an amendment to the Official Brunswick County CAMA Land Use Plan Map for Tax Parcels 2160007604, 2160007605, 2160007608 and 2160007609 located off Stone Chimney Road SW (SR 1115) and Old Ferry Connection Road SW (SR 1115) near Holden Beach from LDR (Low Density Residential) to Commercial.

Mr. Leary made a motion to open the Public Hearing and the motion was unanimously carried.

Mr. Tariq Nizam addressed the Board. Mr. Nizam said they purchased the property with the intention to develop the property for commercial purposes. He stated that there is existing commercial nearby.

Mr. Edward Vanvliet addressed the Board in opposition to the zoning change because he felt that this is a very busy intersection that vacationers utilize while traveling to Holden Beach. Mr. Vanvliet felt a change in the zoning designation to commercial will add more traffic to this area, which is predominantly a residential community. Mr. Vanvliet further stated that the applicant has not indicated his intended use of the property if it is changed to C-LD.

Ms. Easley asked Mr. Vanvliet if he lives in the area and he replied that he lives in Varnamtown and he frequently travels through this area.

Ms. Marva Moss addressed the Board. Ms. Moss asked how the property will be used? Mr. Dunham said any use that is allowed in C-LD would be allowed provided all minimum requirements are met.

Ms. Robin Vanvliet addressed the Board. Ms. Vanvliet asked what the applicant's intent is with the property? Mr. Patton said specific uses cannot be considered by the Board. Ms. Vanvliet reiterated Mr. Vanvliet's concerns of being in opposition to the zoning change. She further stated that there have been multiple accidents at the intersection of Stone Chimney Road SW (SR 1119) and Old Ferry Connection Road SW (SR 1115). Ms. Vanvliet was also concerned with her property value being decreased if the property is zoned C-LD.

With no further comments, Ms. Easley made a motion to close the Public Hearing and the motion was unanimously carried.

Mr. Dunham asked staff if there are any road improvements proposed in the area? Mr. Pages said not at this time, but a North Carolina Department of Transportation (NCDOT) Driveway Permit would be required for any commercial development.

Mr. Dunham asked the applicant if the properties will be combined and Mr. Nizam said yes. Mr. Pages concurred that the tax parcels will have to be combined to develop the property for commercial purposes. Mr. Pages further stated that NCDOT will review the area to determine if any improvements will be necessary at the intersection such as a flashing light, signalization, a 4 way stop sign or deceleration lane.

Ms. Easley made a motion to recommend to the Board of Commissioners to approve Tax Parcels 2160007604, 2160007605, 2160007608 and 2160007609 to C-LD in conjunction with an amendment to the Official Brunswick County CAMA Land Use Plan Map for Tax Parcels 2160007604, 2160007605, 2160007608 and 2160007609 located off Stone Chimney Road SW (SR 1115) and Old Ferry Connection Road SW (SR 1115) near Holden Beach from LDR (Low Density Residential) to Commercial.

THEREFORE, on the basis of all the foregoing, IT IS ORDERED that the ZONING AMENDMENT be recommended to the Board of Commissioners for

APPROVED – NOT CONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment is NOT consistent with the CAMA Land Use Plan (Comprehensive Plan) for the following reasons:

The proposed zoning amendment is not consistent with the CAMA Land Use Plan. However, an amendment has been requested from LDR (Low Density Residential) to Commercial.

- The Planning Board further finds that the approval of the proposed zoning amendment will amend the CAMA Land Use Plan (Comprehensive Plan) and the following changes have been considered to meet the needs of the community:

The CAMA Land Use Plan strongly supports commercial nodes and this area is in transition.

- The Planning further finds that the proposed zoning amendment is reasonable and in the public interest for the following reasons:

The proposed amendment will reduce driveway connections on a heavily traveled road(s).

C. Proposed Unified Development Ordinance Text Amendment to Require Setback Certification

Ms. Dixon addressed the Board. Ms. Dixon stated that the proposed text amendment (attached) will require a foundation survey for new residential principal and accessory structures with certain provisions. She further stated that future inspections would be prohibited until the foundation survey has been received and approved by the Zoning Administrator or designee. Ms. Dixon said a signed and sealed letter from a Professional Land Surveyor identifying the property and structure and certifying that the structure meets or exceeds the setback for the zoning district in which it is located may be provided in lieu of a survey map. Ms. Dixon outlined the exceptions that includes decks, patios, fences, etc. Ms. Dixon said the Board of Adjustment endorses this text amendment as a result of a variance request denial where a minimum setback could not be met because the home was too close to the front property line and the home had to be reconfigured.

Mr. Medlin asked staff if decks and patios are exempted from providing a foundation survey and Ms. Dixon replied yes. Mr. Medlin was concerned with enclosed decks being built without a permit. Ms. Dixon said that language can be changed to exempt just open decks.

After lengthy discussion, regarding whether a survey should be required upfront, Mr. Batton reminded the Board that they have to consider the matter before them that was advertised for a public hearing.

Ms. Easley made a motion to open the Public Hearing and the motion was unanimously carried.

With no further comments, Mr. Leary made a motion to close the Public Hearing and the motion was unanimously carried.

Ms. Easley made a motion to recommend to the Board of Commissioners to approve the Setback Certification Text Amendment with a change in Section 3.1.4.C.d. Setback Certification to say open decks rather than ~~decks~~ are exempt from providing a foundation survey.

THEREFORE, on the basis of all the foregoing, IT IS ORDERED that the ZONING AMENDMENT be recommended to the Board of Commissioners for

APPROVAL – CONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment is consistent with the CAMA Land Use Plan (Comprehensive Plan) for the following reasons:

The proposed zoning amendment is consistent with the CAMA Land Use Plan as there is no impact.

- The Planning Board further finds that the proposed zoning amendment is reasonable and in the public interest for the following reasons:

This amendment will eliminate potential structures from being placed within the setback and eliminate cost to relocate a structure.

VIII. OTHER BUSINESS.

- Mirasol Planned Development (PD-1) Extension Request.

Mr. Pages addressed the Board. He stated that the developer, Malcolm Jones, has requested a 2 year extension for Mirasol Planned Development (PD-1) that was approved on 08-Jun15 as little activity (minimal grading) has occurred on the site. Mr. Pages said staff recommends approval.

Mr. Leary made a motion to approve a 2 year extension for Mirasol Planned Development (PD-1) and the motion was unanimously carried.

- CAMA Core Land Use Plan Status Report

Ms. Dixon addressed the Board. She stated that staff is presenting the Brunswick County CAMA Core Land Use Plan Status Report that is required by the State. Ms. Dixon briefly discussed the Status Report (attached) on the implementation of the Brunswick County CAMA Core Land Use Plan.

- New Staff

Ms. Dixon addressed the Board. She introduced Mr. Brandon Hackney as the Project Planner. Ms. Dixon said Mr. Hackney will be focusing on commercial development projects. The Board welcomed Mr. Hackney to staff.

- Planning Board Cases Update

Ms. Dixon addressed the Board. She stated that zoning cases Z-760 and Z-762 were approved at the Board of Commissioners 23-Apr-18 as well as the Fire Code Text Amendment. Ms. Dixon said zoning case Z-761 was tabled at the 23-Apr-18 meeting because a citizen expressed concerns at that meeting that were later addressed by staff with the citizen. She stated that Z-761 will be considered for approval at the Board of Commissioners' 21-May-18 meeting.

- Planning Board Training

Ms. Dixon addressed the Board. She stated that staff is trying to schedule a training session, but staff did not receive many responses from Board members when the request was sent via a Doodle Survey. Ms. Dixon said staff has selected 31-May-18 and 06-Jun-18 as potential dates for the training. She asked that each Board member get with Mr. Hackney before leaving to provide the best date and time based on the tentative dates and times. She further stated that the Cape Fear Council of Governments will be hosting the event. Ms. Dixon said if the selected dates/times are not conducive to everyone's schedule, staff will select additional dates to accommodate everyone's schedule as much as possible.

IX. ADJOURNMENT.

- With no further business, Mr. Leary made a motion to adjourn and the motion was unanimously carried.

DRAFT

BRUNSWICK COUNTY BUILDING INSPECTIONS

BRUNSWICK COUNTY GOVERNMENT CENTER
BUILDING I
75 COURTHOUSE DRIVE, N.E.
BOLIVIA, NORTH CAROLINA 28422

MAILING ADDRESS:

POST OFFICE BOX 249
BOLIVIA, NORTH CAROLINA 28422

TELEPHONE
(910) 253-2050
(800) 822-5986

FAX
(910) 253-2416

MEMORANDUM

June 11th, 2018

To: Planning Board


Subject: **Proposed Unified Development Ordinance Text Amendment Related to Revisions of the Flood Damage Prevention Ordinance**

The Federal Emergency Management Agency (FEMA) has released the proposed flood map changes related to Brunswick County. FEMA has recognized, through scientific studies and data analysis, a need to revise the current flood maps to protect lives and to minimize property damage during a flood event. Brunswick County must revise the current Flood Damage Prevention Ordinance to address the new flood maps issued by FEMA and to comply with the requirements set forth by the State and FEMA. These changes will comply with the mandated enforcement and better serve the citizenry during a flood event. While the majority of the changes to the Flood Damage Prevention Ordinance are placed for clarification, section H is a new Article to address a new component to the flood maps. Attached is a short description of the need for this addition.

LIMWA and Coastal A Zone Mapping

FEMA has released the new flood maps for Brunswick County and surrounding areas for review and adoption. Brunswick County is currently going through the adoption process for these new maps and the revision of the Flood Damage Prevention Ordinance. A new aspect of the flood maps identified by FEMA is the Limit of Moderate Wave Action (LiMWA).

On previous maps, a VE Zone was mapped as a Coastal High Hazard area that could generate wave action of three (3) feet or higher and an AE Zone is coastal flooding with wave action of less than three (3) feet. FEMA fact sheet states the primary reason for having the two different coastal zones is the risk of structural damage is higher in a VE Zone because of the significant wave energy that can occur in these areas. FEMA recognized through post-storm damage surveys, even wave action as low as 1.5 feet can cause significant damage to structures not built to VE Zone standards.



This Limit of Moderate Wave Action (LiMWA) can be identified on the new maps by the line placed between the edge of the VE Zone and AE Zone. All

area between the VE Zone and the LiMWA line is the area where wave action can be between 1.5 and 3 feet.



Based on the information proved by FEMA and the recognition of the potential for significant damage to structures in this area, Brunswick County has elected to adopt the FEMA suggested requirements for non-residential newly built or substantially improved structures in this area. The requirement to enforce the regulations is not option but can be tailored to meet the County's needs.

The following is the Flood Damage Prevention Ordinance pertaining to LiMWA:

H. Standards for Coastal A Zones (Zone CAZ) LiMWA (LIMIT OF MODERATE WAVE ACTION)

Non-residential structures in CAZs shall be designed and constructed to meet V Zone requirements, including requirements for breakaway walls. However, the NFIP regulations also require flood openings in walls surrounding enclosures below elevated buildings in CAZs (see Technical Bulletin 1, Openings in Foundation Walls and Walls of Enclosures). Breakaway walls used in CAZs must have flood openings that allow for the automatic entry and exit of floodwaters to minimize damage caused by hydrostatic loads. Openings also function during smaller storms or if anticipated wave loading does not occur with the base flood.

- (1) All new non-residential construction and substantial improvements shall be elevated so that the bottom of the lowest horizontal structural member of the lowest floor (excluding pilings or columns) is no lower than the regulatory flood protection elevation. Floodproofing shall not be utilized on any structures in Coastal A Zones to satisfy the regulatory flood protection elevation requirements.

- (2) All new non-residential construction and substantial improvements shall have the space below the lowest horizontal structural member free of obstruction so as not to impede the flow of flood waters, with the following exceptions:
 - (a) Open wood latticework or insect screening may be permitted below the lowest floor for aesthetic purposes only and must be designed to wash away in the event of wave impact and in accordance with the provisions of Article 7.1.5, Section B(4)(e)(i). Design plans shall be submitted in accordance with the provisions of Article 7.1.4, Section B(1)(d)(iii)(2); or
 - (b) Breakaway walls may be permitted provided they meet the criteria set forth in Article 7.1.5, Section B(4)(e)(ii). Design plans shall be submitted in accordance with the provisions of Article 7.1.4, Section B(1)(d)(iii)(1).
- (3) All new construction and substantial improvements shall include, in Zones CAZ, flood openings to automatically equalize hydrostatic flood forces on walls by allowing for the entry and exit of floodwaters. To meet this requirement, the openings must either be certified by a professional engineer or architect or meet or exceed the design criteria in Article 7.1.5, Section B(4)(d).
- (4) Concrete pads, including patios, decks, parking pads, walkways, driveways, etc. must meet the provisions of Article 7.1.5, Section G(5).
- (5) All new non-residential construction and substantial improvements shall meet the provisions of Article 7.1.5, Section G(3)
- (6) A registered professional engineer or architect shall certify that the design, specifications and plans for construction are in compliance with the provisions of Article 7.1.4, Section B and Article 7.1.5, Section G(3) and (4), on the current version of the North Carolina V-Zone Certification form or a locally developed V-Zone Certification form.
- (7) Recreational vehicles may be permitted in Coastal A Zones provided that they meet the Recreational Vehicle criteria of Article 7.1.5, Section B(6)(a).
- (8) Fill/Grading must meet the provisions of Article 7.1.5, Section G(11)
- (9) Decks and patios must meet the provisions of Article 7.1.5 Section G(15) and (16).
- (10) In coastal high hazard areas, development activities other than buildings and structures must meet the provisions of Article 7.1.5, Section G(17)

BRUNSWICK COUNTY FLOOD DAMAGE PREVENTION ORDINANCE

ARTICLE 7. - FLOOD DAMAGE PREVENTION

7.1 - FLOOD DAMAGE PREVENTION ORDINANCE (AUGUST 28, 2018)

7.1.1. Statutory Authorization

~~The Legislature of the State of North Carolina has in Part 6, Article 21 of Chapter 143; Parts 3 and 4 of Article 18 of Chapter 153A; and Part 121, [Article 6](#) of Chapter 153A of the North Carolina General Statutes, delegated to local governmental the responsibility units to adopt regulations designed to promote the public health, safety, and general welfare of its citizenry.~~

The Legislature of the State of North Carolina has in Part 6, Article 21 of Chapter 143; Parts 3 and 4 of Article 18 of Chapter 153A; and Part 121, Article 6 of Chapter 153A of the North Carolina General Statutes, delegated to local governmental units the responsibility to adopt regulations designed to promote the public health, safety, and general welfare.

~~Therefore, the Board of Commissioners of Brunswick County, North Carolina, does ordain as follow:~~

Therefore, the Governing Body of Brunswick County, North Carolina, does ordain as follows:

A. Finding of Facts

- (1) The flood prone areas within the jurisdiction of Brunswick County are subject to periodic inundation which results in loss of life, property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures of flood protection and relief, and impairment of the tax base, all of which adversely affect the public health, safety, and general welfare.
- (2) These flood losses are caused by the cumulative effect of obstructions in floodplains causing increases in flood heights and velocities and by the occupancy in flood prone areas of uses vulnerable to floods or other hazards.

B. Statement of Purpose

It is the purpose of this ordinance to promote public health, safety, and general welfare and to minimize public and private losses due to flood conditions within flood prone areas by provisions designed to:

- (1) Restrict or prohibit uses that are dangerous to health, safety, and property due to water or erosion hazards or that result in damaging increases in erosion, flood heights or velocities;
- (2) Require that uses vulnerable to floods, including facilities that serve such uses, be protected against flood damage at the time of initial construction;
- (3) Control the alteration of natural floodplains, stream channels, and natural protective barriers, which are involved in the accommodation of floodwaters;
- (4) Control filling, grading, dredging, and all other development that may increase erosion or flood damage; and;
- (5) Prevent or regulate the construction of flood barriers that will unnaturally divert flood waters or which may increase flood hazards to other lands.

C. Objectives

The objectives of this ordinance are to:

1. ~~Fe~~ Protect human life and health;
2. ~~Fe~~ Minimize expenditure of public money for costly flood control projects;
3. ~~Fe~~ Minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the general public;
4. ~~Fe~~ Minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the general public;
5. ~~Fe~~ Minimize damage to public facilities and utilities (i.e. water and gas mains, electric, telephone, cable and sewer lines, streets, and bridges) that are located in flood prone areas;
6. Minimize damage to private and public property due to flooding;
7. Make flood insurance available to the community through the National Flood Insurance Program;
8. Maintain the natural and beneficial functions of floodplains;
9. Help maintain a stable tax base by providing for the sound use and development of flood prone areas; and
10. Ensure that potential buyers are aware that property is in a Special Flood Hazard Area.

7.1.2. Definitions

~~For the purposes of this Section (Flood Damage Prevention), words and phrases are defined as follows. Unless specifically defined below, words or phrases used in this Ordinance shall be interpreted so as to give them the meaning they have in common usage and to give this Ordinance its most reasonable application.~~

Unless specifically defined below, word or phrases used in the Flood Damage Prevention ordinance shall be interpreted so as to give them the meaning they have in common usage and to give its most reasonable application.

“Accessory Structure (Appurtenant Structure)”: a structure located on the same parcel of property as the principal structure and the use of which is incidental to the use of the principal structure. Garages, carports and storage sheds are common urban accessory structures. Pole barns, hay sheds and the like qualify as accessory structures on farms, and may or may not be located on the same parcel as the farm dwelling or shop building.

“Addition (to an existing building)”: an extension or increase in the floor area or height of a building or structure.

Alteration of a watercourse: a dam, impoundment, channel relocation, change in channel alignment, channelization, or change in cross-sectional area of the channel or the channel capacity, or any other form of modification which may alter, impede, retard or change the direction and/or velocity of the riverine flow of water during conditions of the base flood.

Appeal: a request for a review of the Floodplain Administrator's interpretation of any provision of the Flood Damage Prevention Ordinance.

~~Area of Shallow Flooding: a designated Zone AO or AH on a community's Flood Insurance Rate Map (FIRM) with base flood depths determined to be from one (1) to three (3) feet. These areas are located where a clearly defined channel does not exist, where the path of flooding is unpredictable and indeterminate, and where velocity flow may be evident.~~

Area of Special Flood Hazard: see “Special Flood Hazard Area (SFHA)”.

Area of Future-Conditions Flood Hazard: the land area that would be inundated by the 1-percent-annual-chance (100-year) flood based on future-conditions hydrology.

Base Flood: the flood having a one (1) percent chance of being equaled or exceeded in any given year.

Base Flood Elevation (BFE): a determination of the water surface elevations of the base flood as published in the Flood Insurance Study. When the BFE has not been provided in a "Special Flood Hazard Area", it may be obtained from engineering studies available from a Federal, State, or other source using FEMA approved engineering methodologies. This elevation, when combined with the "Freeboard", establishes the "Regulatory Flood Protection Elevation".

Basement: any area of the building having its floor subgrade (below ground level) on all sides.

Breakaway Wall: a wall that is not part of the structural support of the building and is intended through its design and construction to collapse under specific lateral loading forces without causing damage to the elevated portion of the building or the supporting foundation system.

Building: see "Structure".

Chemical Storage Facility: a building, portion of a building, or exterior area adjacent to a building used for the storage of any chemical or chemically reactive products.

~~CAMA: North Carolina's Coastal Area Management Act. This act, along with the Dredge and Fill Law and the federal Coastal Zone Management Act, is managed through North Carolina Department of Environment and Natural Resources' (NCDENR's) Division of Coastal Management (DCM).~~

Coastal Area Management Act (CAMA): North Carolina's Coastal Area Management Act, this act, along with the Dredge and Fill Law and the Federal Coastal Zone Management Act, is managed through North Carolina Department of Environment and Natural Resources' (NCDENR's) Division of Coastal Management (DCM).

Coastal A Zone (CAZ): an area within a special flood hazard area, landward of a V zone or landward of an open coast without mapped V zones; in a Coastal A Zone, the principal source of flooding must be astronomical tides, storm surges, seiches, or tsunamis, not riverine flooding. During the base flood conditions, the potential for wave heights shall be greater than or equal to 1.5 feet. Coastal A Zones are not normally designated on FIRMs. (see Limit of Moderate Wave Action (LiMWA))

~~Coastal Barrier Resources System (CBRS): Consists of undeveloped portions of coastal and adjoining areas established by the Coastal Barrier Resources Act (CoBRA) of 1982, the Coastal Barrier Improvement Act (CBIA) of 1990, and subsequent revisions, and includes areas owned by federal or state governments or private conservation organizations identified as Otherwise Protected Areas (OPA).~~

Coastal Barrier Resources System (CBRS): undeveloped portions of coastal and adjoining areas established by the Coastal Barrier Resources Act (CoBRA) of 1982, the Coastal Barrier Improvement Act (CBIA) of 1990, and subsequent revisions, and includes areas owned by Federal or State governments or private conservation organizations identified as Otherwise Protected Areas (OPA).

Coastal High Hazard Area: a Special Flood Hazard Area extending from offshore to the inland limit of a primary frontal dune along an open coast and any other area subject to high velocity wave action from storms or seismic sources. The area is designated on a FIRM, or other adopted flood map as determined in Article 7.1.1, Section B of this ordinance, as Zone VE.

Design Flood: see “Regulatory Flood Protection Elevation.”

Development: any man-made change to improved or unimproved real estate, including, but not limited to, buildings or other structures, mining, dredging, filling, grading, paving, excavation or drilling operations, or storage of equipment or materials.

Development Activity: any activity defined as Development which will necessitate a Floodplain Development Permit. This includes buildings, structures, and non-structural items, including (but not limited to) fill, bulkheads, piers, pools, docks, landings, ramps, and erosion control/stabilization measures.

Digital Flood Insurance Rate Map (DFIRM): the digital official map of a community, issued by the Federal Emergency Management Agency (FEMA), on which both the Special Flood Hazard Areas and the risk premium zones applicable to the community are delineated.

Disposal: as defined in NCGS 130A-290(a)(6), the discharge, deposit, injection, dumping, spilling, leaking, or placing of any solid waste into or on any land or water so that the solid waste or any constituent part of the solid waste may enter the environment or be emitted into the air or discharged into any waters, including groundwaters.

Elevated Building: a non-basement building which has its lowest elevated floor raised above ground level by foundation walls, shear walls, posts, piers, pilings, or columns.

Encroachment: the advance or infringement of uses, fill, excavation, buildings, structures or development into a special flood hazard area, which may impede or alter the flow capacity of a floodplain.

Existing building and existing structure: any building and/or structure for which the “start of construction” commenced before date the community’s first floodplain management ordinance was adopted.

Existing Manufactured Home Park or Manufactured Home Subdivision: a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including, at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) was completed before the initial effective date of the floodplain management regulations adopted by the community.

Flood or Flooding: a general and temporary condition of partial or complete inundation of normally dry land areas from:

- (1) The overflow of inland or tidal waters; and/or
- (2) The unusual and rapid accumulation or runoff of surface waters from any source.

Flood Boundary and Floodway Map (FBFM): an official map of a community, issued by the FEMA, on which the Special Flood Hazard Areas and the floodways are delineated. This official map is a supplement to and shall be used in conjunction with the Flood Insurance Rate Map (FIRM).

Flood Hazard Boundary Map (FHBM): an official map of a community, issued by the FEMA, where the boundaries of the Special Flood Hazard Areas have been defined as Zone A.

Flood Insurance: the insurance coverage provided under the National Flood Insurance Program.

Flood Insurance Rate Map (FIRM): an official map of a community, issued by the FEMA, on which both the Special Flood Hazard Areas and the risk premium zones applicable to the community are delineated. (see also DFIRM)

Flood Insurance Study (FIS): an examination, evaluation, and determination of flood hazards, corresponding water surface elevations (if appropriate), flood hazard risk zones, and other flood data in a community issued by the FEMA. The Flood Insurance Study report includes Flood Insurance Rate Maps (FIRMs) and Flood Boundary and Floodway Maps (FBFMs), if published.

Flood Prone Area: see "Floodplain"

Flood Zone: a geographical area shown on a Flood Hazard Boundary Map or Flood Insurance Rate Map that reflects the severity or type of flooding in the area.

Floodplain: any land area susceptible to being inundated by water from any source.

Floodplain Administrator: the individual appointed to administer and enforce the floodplain management regulations.

Floodplain Development Permit: any type of permit that is required in conformance with the provisions of this ordinance, prior to the commencement of any development activity.

Floodplain Management: the operation of an overall program of corrective and preventive measures for reducing flood damage and preserving and enhancing, where possible, natural resources in the floodplain, including, but not limited to, emergency preparedness plans, flood control works, floodplain management regulations, and open space plans.

Floodplain Management Regulations: this ordinance and other zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances, and other applications of police power. This term describes federal, state or local regulations, in any combination thereof, which provide standards for preventing and reducing flood loss and damage.

Floodproofing: any combination of structural and nonstructural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitation facilities, structures, and their contents.

Flood-resistant material: any building product [material, component or system] capable of withstanding direct and prolonged contact (minimum 72 hours) with floodwaters without sustaining damage that requires more than low-cost cosmetic repair. Any material that is water-soluble or is not resistant to alkali or acid in water, including normal adhesives for above grade use, is not flood-resistant. Pressure-treated lumber or naturally decay-resistant lumbers are acceptable flooring materials. Sheet-type flooring coverings that restrict evaporation from below and materials that are impervious, but dimensionally unstable are not acceptable. Materials that absorb or retain water excessively after submergence are not flood-resistant. Please refer to Technical Bulletin 2, Flood Damage-Resistant Materials Requirements, and available from the FEMA. Class 4 and 5 materials, referenced therein, are acceptable flood-resistant materials.

Floodway: The channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one (1) foot.

Floodway: the channel of a river or other watercourse, including the area above a bridge or culvert when applicable, and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one (1) foot.

Floodway encroachment analysis: an engineering analysis of the impact that a proposed encroachment into a floodway or non-encroachment area is expected to have on the floodway boundaries and flood levels during the occurrence of the base flood discharge. The evaluation shall be prepared by a qualified North Carolina licensed engineer using standard engineering methods and models.

Freeboard: the height added to the BFE to account for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as wave action, blockage of bridge or culvert openings, and the hydrological effect of urbanization of the watershed. The BFE plus the freeboard establishes the “Regulatory Flood Protection Elevation”.

Functionally Dependent Facility: a facility which cannot be used for its intended purpose unless it is located in close proximity to water, limited to a docking or port facility necessary for the loading and unloading of cargo or passengers, shipbuilding, or ship repair. The term does not include long-term storage, manufacture, sales, or service facilities.

Hazardous Waste Management Facility: as defined in NCGS 130A, Article 9, a facility for the collection, storage, processing, treatment, recycling, recovery, or disposal of hazardous waste.

Highest Adjacent Grade (HAG): the highest natural elevation of the ground surface, prior to construction, immediately next to the proposed walls of the structure.

Historic Structure: any structure that is:

- (1) Listed individually in the National Register of Historic Places (a listing maintained by the US Department of Interior) or preliminarily determined by the Secretary of Interior as meeting the requirements for individual listing on the National Register;
- (2) Certified or preliminarily determined by the Secretary of Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district;
- (3) Individually listed on a local inventory of historic landmarks in communities with a “Certified Local Government (CLG) Program”; or
- (4) Certified as contributing to the historical significance of a historic district designated by a community with a “Certified Local Government (CLG) Program.”

Certified Local Government (CLG) Programs are approved by the US Department of the Interior in cooperation with the North Carolina Department of Cultural Resources through the State Historic Preservation Officer as having met the requirements of the National Historic Preservation Act of 1966 as amended in 1980.

Letter of Map Change (LOMC): an official determination issued by FEMA that amends or revises an effective Flood Insurance Rate Map or Flood Insurance Study. Letters of Map Change include:

- (1) Letter of Map Amendment (LOMA): An official amendment, by letter, to an effective National Flood Insurance Program map. A LOMA is based on technical data showing that a property had been inadvertently mapped as being in the floodplain, but is actually on natural high ground above the base flood

elevation. A LOMA amends the current effective Flood Insurance Rate Map and establishes that a specific property, portion of a property, or structure is not located in a special flood hazard area.

- (2) Letter of Map Revision (LOMR): A revision based on technical data that may show changes to flood zones, flood elevations, special flood hazard area boundaries and floodway delineations, and other planimetric features.
- (3) Letter of Map Revision Based on Fill (LOMR-F): A determination that a structure or parcel of land has been elevated by fill above the BFE and is, therefore, no longer located within the special flood hazard area. In order to qualify for this determination, the fill must have been permitted and placed in accordance with the community's floodplain management regulations.
- (4) Conditional Letter of Map Revision (CLOMR): A formal review and comment as to whether a proposed project complies with the minimum NFIP requirements for such projects with respect to delineation of special flood hazard areas. A CLOMR does not revise the effective Flood Insurance Rate Map or Flood Insurance Study; upon submission and approval of certified as-built documentation, a Letter of Map Revision may be issued by FEMA to revise the effective FIRM.

Light Duty Truck: any motor vehicle rated at 8,500 pounds Gross Vehicular Weight Rating or less which has a vehicular curb weight of 6,000 pounds or less and which has a basic vehicle frontal area of 45 square feet or less as defined in 40 CFR 86.082-2 and is:

- (1) Designed primarily for purposes of transportation of property or is a derivation of such a vehicle, or
- (2) Designed primarily for transportation of persons and has a capacity of more than 12 persons; or
- (3) Available with special features enabling off-street or off-highway operation and use.

Limit of Moderate Wave Action: the boundary line given by FEMA on coastal map studies marking the extents of Coastal A Zones (CAZ).

Lowest Adjacent Grade (LAG): the lowest elevation of the ground, sidewalk or patio slab immediately next to the building, or deck support, after completion of the building.

Lowest Floor: the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, usable solely for parking of vehicles, building access, or limited storage in an area other than a basement area is not considered a building's lowest floor, provided that such an enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements of this ordinance.

Manufactured Home: a structure, transportable in one or more sections, which is built on a permanent chassis and designed to be used with or without a permanent foundation when connected to the required utilities. The term "manufactured home" does not include a "recreational vehicle".

Manufactured Home Park or Subdivision: a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

Market Value: the building value, not including the land value and that of any accessory structures or other improvements on the lot. Market value may be established by independent certified appraisal; replacement cost depreciated for age of building and quality of construction (Actual Cash Value); or adjusted tax assessed values.

Mean Sea Level: for purposes of this ordinance, the North American Vertical Datum (NAVD) as corrected in 1988, to which Base Flood Elevations (BFEs) shown on a DFIRM are referenced. North Carolina uses NAVD 1988.

New Construction: structures for which the "start of construction" commenced on or after the effective date of

the initial floodplain management regulations and includes any subsequent improvements to such structures.

~~Non-Conversion Agreement: a document stating that the owner will not convert or alter what has been constructed and approved. Violation of the agreement is considered a violation of the ordinance and, therefore, subject to the same enforcement procedures and penalties. The agreement must be filed with the recorded deed for the property. The agreement must show the clerk's or recorder's stamps and/or notations that the filing has been completed. (OPTIONAL)~~

Non-Encroachment Area (NEA): the channel of a river or other watercourse, including the area above a bridge or culvert when applicable, and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one (1) foot as designated in the Flood Insurance Study report.

~~OPA: An Otherwise Protected Area~~

Otherwise Protected Area: see "Coastal Barrier Resources System (CBRS)".

Post-FIRM: construction or other development for which the "start of construction" occurred on or after May 15th, 1986, the effective date of the initial Flood Insurance Rate Map.

Pre-FIRM: construction or other development for which the "start of construction" occurred before May 15th, 1986, the effective date of the initial Flood Insurance Rate Map.

~~Primary Frontal Dune: A continuous or nearly continuous mound or ridge of sand with relatively steep seaward and landward slopes immediately landward and adjacent to the beach and subject to erosion and overtopping from high tides and waves during major coastal storms. The inland limit of the primary frontal dune occurs at the point where there is a distinct change from a relatively steep slope to a relatively mild slope.~~

Primary Frontal Dune (PFD): a continuous or nearly continuous mound or ridge of sand with relatively steep seaward and landward slopes immediately landward and adjacent to the beach and subject to erosion and overtopping from high tides and waves during major coastal storms. The inland limit of the primary frontal dune occurs at the point where there is a distinct change from a relatively steep slope to a relatively mild slope.

Principally Above Ground: at least 51% of the actual cash value of the structure is above ground.

Public Safety and/or Nuisance: anything which is injurious to the safety or health of an entire community or neighborhood, or any considerable number of persons, or unlawfully obstructs the free passage or use, in the customary manner, of any navigable lake, or river, bay, stream, canal, or basin.

Recreational Vehicle (RV): A vehicle, which is:

- ~~(1) Built on a single chassis;~~
- ~~(2) 400 square feet or less when measured at the largest horizontal projection;~~
- ~~(3) Designed to be self-propelled or permanently towable by a light duty truck; and~~
- ~~(4) Designed primarily not for use as a permanent dwelling, but as temporary living quarters for recreational, camping, travel, or seasonal use.~~

Recreational Vehicle (RV): a vehicle, which is:

- (1) Built on a single chassis;
- (2) 400 square feet or less when measured at the largest horizontal projection;
- (3) Designed to be self-propelled or permanently towable by a light duty truck;
- (4) Designed primarily not for use as a permanent dwelling, but as temporary living quarters for recreational, camping, travel, or seasonal use, and
- (5) Is fully licensed and ready for highway use.

(Tiny Homes/Houses” and Park Models that do not meet the items listed above are not considered Recreational Vehicles and should meet the standards of and be permitted as Residential Structures.) (OPTIONAL)

Reference Level: the top of the lowest floor for structures within Special Flood Hazard Areas designated as Zones A, AE, AH, AO, A99. The reference level is the bottom of the lowest horizontal structural member of the lowest floor for structures within Special Flood Hazard Areas designated as Zone VE.\

~~Regulatory Flood Protection Elevation: The "Base Flood Elevation" plus the "Freeboard". In "Special Flood Hazard Areas" where Base Flood Elevations (BFEs) have been determined, this elevation shall be the BFE plus two (2) feet of freeboard. In "Special Flood Hazard Areas" where no BFE has been established, this elevation shall be at least two (2) feet above the highest adjacent grade.~~

Regulatory Flood Protection Elevation: the “Base Flood Elevation” plus the “Freeboard”. In “Special Flood Hazard Areas” where Base Flood Elevations (BFEs) have been determined, this elevation shall be the BFE plus (2) feet freeboard). In “Special Flood Hazard Areas” where no BFE has been established, this elevation shall be at least than two (2) feet above the highest adjacent grade.

Remedy a Violation: to bring the structure or other development into compliance with state and community floodplain management regulations, or, if this is not possible, to reduce the impacts of its noncompliance. Ways that impacts may be reduced include protecting the structure or other affected development from flood damages, implementing the enforcement provisions of the ordinance or otherwise deterring future similar violations, or reducing federal financial exposure with regard to the structure or other development.

Riverine: relating to, formed by, or resembling a river (including tributaries), stream, brook, etc.

Salvage Yard: any non-residential property used for the storage, collection, and/or recycling of any type of equipment, and including but not limited to vehicles, appliances and related machinery.

Sand Dunes: naturally occurring accumulations of sand in ridges or mounds landward of the beach.

Shear Wall: walls used for structural support but not structurally joined or enclosed at the end (except by breakaway walls). Shear walls are parallel or nearly parallel to the flow of the water.

Solid Waste Disposal Facility: any facility involved in the disposal of solid waste, as defined in NCGS 130A-290(a)(35).

Solid Waste Disposal Site: as defined in NCGS 130A-290(a)(36), any place at which solid wastes are disposed of by incineration, sanitary landfill, or any other method.

Special Flood Hazard Area (SFHA): the land in the floodplain subject to a one percent (1%) or greater chance of being flooded in any given year, as determined in Article 7.1.1, Section B of this ordinance.

Start of Construction: includes substantial improvement, and means the date the building permit was issued provided the actual start of construction, repair, reconstruction, rehabilitation, addition placement, or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading, and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of the building, whether or not that alteration affects the external dimensions of the building.

Structure: a walled and roofed building, a manufactured home, or a gas, liquid, or liquefied gas storage tank that is principally above ground.

~~Substantial Damage: Damage of any origin sustained by a structure during any one-year period whereby the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred. See definition of "substantial improvement".~~

Substantial Damage: damage of any origin sustained by a structure during any one-year period whereby the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred. See definition of "substantial improvement". [CRS communities are eligible for up to 20 CRS points for adopting OPTIONAL Text for Substantial Damage that could include the following higher standards:

- (1) Substantial damage also means flood-related damage sustained by a structure on two separate occasions during a 10-year period for which the cost of repairs at the time of each such flood event, on the average, equals or exceeds 25 percent of the market value of the structure before the damage occurred.

~~Substantial Improvement: Any combination of repairs, reconstruction, rehabilitation, addition, or other improvement of a structure, taking place during any one-year period for which the cost equals or exceeds 50 percent of the market value of the structure before the "start of construction" of the improvement. This term includes structures which have incurred "substantial damage", regardless of the actual repair work performed. The term does not, however, include either:~~

- ~~(1) Any correction of existing violations of State or community health, sanitary, or safety code specifications which have been identified by the community code enforcement official and which are the minimum necessary to assure safe living conditions, or~~
- ~~(2) Any alteration of a historic structure, provided that the alteration will not preclude the structure's continued designation as a historic structure.~~

Substantial Improvement: any combination of repairs, reconstruction, rehabilitation, addition, or other improvement of a structure, taking place during any one-year period for which the cost equals or exceeds 50 percent of the market value of the structure before the "start of construction" of the improvement. This term includes structures which have incurred "substantial damage", regardless of the actual repair work performed. The term does not, however, include either:

- (1) Any correction of existing violations of state or community health, sanitary, or safety code specifications which have been identified by the community code enforcement official and which are the minimum necessary to assure safe living conditions; or
- (2) Any alteration of a historic structure, provided that the alteration will not preclude the structure's continued designation as a historic structure and the alteration is approved by variance issued pursuant to Article 7.1.4 Section E of this ordinance.

Technical Bulletin and Technical Fact Sheet: a FEMA publication that provides guidance concerning the building performance standards of the NFIP, which are contained in Title 44 of the U.S. Code of Federal Regulations at Section 60.3. The bulletins and fact sheets are intended for use primarily by State and local officials responsible for interpreting and enforcing NFIP regulations and by members of the development community, such as design professionals and builders. New bulletins, as well as updates of existing bulletins, are issued periodically as needed. The bulletins do not create regulations; rather they provide specific guidance for complying with the minimum requirements of existing NFIP regulations. It should be noted that Technical Bulletins and Technical Fact Sheets provide guidance on the minimum requirements of the NFIP regulations. State or community requirements that exceed those of the NFIP take precedence. Design professionals should contact the community officials to determine whether more restrictive State or local regulations apply to the building or site in question. All applicable standards of the State or local building code must also be met for any building in a flood hazard area.

Temperature Controlled: having the temperature regulated by a heating and/or cooling system, built-in or appliance.

Variance: a grant of relief from the requirements of this ordinance.

Violation: the failure of a structure or other development to be fully compliant with the community's floodplain management regulations. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in Articles 7.1.4 and 7.1.5 is presumed to be in violation until such time as that documentation is provided.

Water Surface Elevation (WSE): the height, in relation to NAVD 1988, of floods of various magnitudes and frequencies in the floodplains of coastal or riverine areas.

Watercourse: a lake, river, creek, stream, wash, channel or other topographic feature on or over which waters flow at least periodically. Watercourse includes specifically designated areas in which substantial flood damage may occur.

7.1.3. General Provisions

A. Applicability

~~This ordinance shall apply to all Special Flood Hazard Areas within the jurisdiction, including Extra-Territorial Jurisdictions (ETJs) if applicable, of all municipalities and within the jurisdiction of any other community whose governing body agrees, by resolution, to such applicability.~~

This ordinance shall apply to all Special Flood Hazard Areas within the jurisdiction, including Extra-Territorial Jurisdictions (ETJs) of Brunswick County.

B. Basis for Establishing the Special Flood Hazard Area

~~The Special Flood Hazard Areas are those identified under the Cooperating Technical State (CTS) agreement between the State of North Carolina and FEMA in its Flood Insurance Study (FIS) and its accompanying Flood~~

~~Insurance Rate Maps (FIRM), for the unincorporated area of Brunswick County dated October 16, 2008, which are adopted by reference and declared to be a part of this Ordinance and letter of map changes.~~

~~The Special Flood Hazard Areas are those identified under the Cooperating Technical State (CTS) agreement between the State of North Carolina and FEMA in its FIS dated August 28, 2018 for Brunswick County and associated DFIRM panels, including any digital data developed as part of the FIS, which are adopted by reference and declared a part of the Flood Damage Prevention Ordinance. Future revisions to the FIS and DFIRM panels that do not change flood hazard data within the jurisdictional authority of Brunswick County are also adopted by reference and declared a part of the Flood Damage Prevention Ordinance. Subsequent Letter of Map Revisions (LOMRs) and/or Physical Map Revisions (PMRs) shall be adopted within 3 months.~~

C. Establishment of Floodplain Development Permit

A Floodplain Development Permit shall be required in conformance with the provisions of the Flood Damage Prevention Ordinance prior to the commencement of any development activities within Special Flood Hazard Areas determined in accordance with Article 7.1.3, Section B of this ordinance.

D. Compliance

No structure or land shall hereafter be located, extended converted, altered, or developed in any way without full compliance with the terms of this ordinance and other applicable regulations.

E. Abrogation and Greater Restrictions

The Flood Damage Prevention Ordinance is not intended to repeal, abrogate, or impair any existing easements, covenants, or deed restrictions. However, where this Ordinance and another conflict or overlap, whichever imposes the more stringent restrictions shall prevail.

F. Interpretation

In the interpretation and application of this Ordinance, all provisions shall be:

- (a) Considered as minimum requirements;
- (b) Liberally construed in favor of the governing body; and
- (c) Deemed neither to limit nor repeal any other powers granted under state statutes.

G. Warning and Disclaimer Liability

The degree of flood protection required by Flood Damage Prevention Ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering consideration. Larger floods can and will occur. Actual flood heights may be increased by man-made or natural causes. This ordinance does not imply that land outside the Special Flood Hazard Areas or uses permitted within such areas will be free from flooding or flood damages. This ordinance shall not create liability on the part of Brunswick County or by any officer or employee thereof for any flood damages that result from reliance on this Ordinance or any administrative decision lawfully made hereunder.

H. Penalties for Violation

~~Violation of the provisions of this Ordinance or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance or special exceptions, shall constitute a misdemeanor. Any person who violates this Ordinance or fails to comply with any of its requirements shall, upon conviction thereof, be fined not more than \$500.00 or imprisoned for not more than 30 days, or both. Each day such violation continues shall be considered a separate offense. Nothing herein contained shall prevent Brunswick County unincorporated area from taking such other lawful action as is necessary to prevent or remedy any violation.~~

Violation of the provisions of The Flood Damage Prevention Ordinance or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance or special exceptions, shall constitute a Class 1 misdemeanor pursuant to NC G.S. § 143-215.58. Any person who violates this ordinance or fails to comply with any of its requirements shall, upon conviction thereof, be fined not more than \$200.00 or imprisoned for not more than thirty (30) days, or both. Each day such violation continues shall be considered a separate offense. Nothing herein contained shall prevent Brunswick County from taking such other lawful action as is necessary to prevent or remedy any violation.

7.1.4. Administration

~~The Director of Building Inspections, hereinafter referred to as the "Floodplain Administrator", is hereby appointed to administer and implement the provisions of this Ordinance or his designee.~~

A. Designation of Floodplain Administrator

The Director of Code Administration, hereinafter referred to as the "Floodplain Administrator", is hereby appointed to administer and implement the provisions of this ordinance. In Instances where the Floodplain Administrator receives assistance from others to complete tasks to administrator and implement this ordinance, the Floodplain Administrator shall be responsible for the coordination and community's overall compliance with the National Flood Insurance Program and the provisions of this ordinance.

B. Floodplain Development Application, Permit, and Certification Requirements

(a) Application Requirements

Application for a Floodplain Development Permit shall be made to the Floodplain Administrator prior to any development activities located within Special Flood Hazard Areas. The following items shall be presented to the Floodplain Administrator to apply for a floodplain development permit:

- (a) A plot plan drawn to scale which shall include, but shall not be limited to, the following specific details of the proposed floodplain development:
 - i. The nature, location, dimensions, and elevations of the area of development/disturbance; existing and proposed structures, utility systems, grading/pavement areas, fill materials, storage areas, drainage facilities, and other development;
 - ii. The boundary of the Special Flood Hazard Area as delineated on the FIRM or other flood map as determined in Article 7.1.3, Section B, or a statement that the entire lot is within the Special Flood Hazard Area;
 - iii. Flood zone(s) designation of the proposed development area as determined on the FIRM or other flood map as determined in Article 7.1.3, Section B;
 - iv. The boundary of the floodway(s) or non-encroachment area(s) as determined in Article 7.1.3, Section B;
 - v. The Base Flood Elevation (BFE) where provided as set forth in Article 7.1.3, Section B; Article 7.1.4, Section C; or Article 7.1.5, Section D;
 - vi. The old and new location of any watercourse that will be altered or relocated as a result of proposed development; and
 - vii. The boundary and designation date of the Coastal Barrier Resource System (CBRS) area or Otherwise Protected Areas (OPA), if applicable; and

- viii. The certification of the plot plan by a registered land surveyor or professional engineer maybe required at the discretion of the floodplain administrator.
- (b) Proposed elevation, and method thereof, of all development within a Special Flood Hazard Area including but not limited to:
- i. Elevation in relation to NAVD 1988 of the proposed reference level (including basement) of all structures;
 - ii. Elevation in relation to NAVD 1988 to which any non-residential structure in Zones A, AE, AH, AO, A99 will be floodproofed; and
 - iii. Elevation in relation to NAVD 1988 to which any proposed utility systems will be elevated or floodproofed.
- (c) If floodproofing, a Floodproofing Certificate (FEMA Form 086-0-34) with supporting data, an operational plan, and an inspection and maintenance plan that include, but are not limited to, installation, exercise, and maintenance of floodproofing measures.
- (d) A Foundation Plan, drawn to scale, which shall include details of the proposed foundation system to ensure all provisions of this ordinance are met. These details include but are not limited to:
- i. The proposed method of elevation, if applicable (i.e., fill, solid foundation perimeter wall, solid backfilled foundation, open foundation on columns/posts/piers/piles/shear walls); and
 - ii. Openings to facilitate automatic equalization of hydrostatic flood forces on walls in accordance with Article 7.1.5, Section B(4)(c) when solid foundation perimeter walls are used in Zones A, AE, AH, A1-30, A99.
 - iii. The following, in Coastal High Hazard Areas, in accordance with the provisions of Article 7.1.5, Section B(4)(e) and Article 7.1.5 Section G and H:
 - (1) V-Zone Certification with accompanying plans and specifications verifying the engineered structure and any breakaway wall designs; In addition, prior to the Certificate of Compliance/Occupancy issuance, a registered professional engineer or architect shall certify the finished construction is compliant with the design, specifications and plans for VE Zone construction;
 - (2) Plans for open wood latticework or insect screening, if applicable; and
 - (3) Plans for non-structural fill, if applicable. If non-structural fill is proposed, it must be demonstrated through coastal engineering analysis that the proposed fill would not result in any increase in the BFE or otherwise cause adverse impacts by wave ramping and deflection on to the subject structure or adjacent properties.
- (e) Usage details of any enclosed areas below the lowest floor.
- (f) Plans and/or details for the protection of public utilities and facilities such as sewer, gas, electrical, and water systems to be located and constructed to minimize flood damage.
- (g) Certification that all other Local, State and Federal permits required prior to floodplain development permit issuance have been received.

- (h) Documentation for placement of Recreational Vehicles and/or Temporary Structures, when applicable, to ensure that the provisions of Article 7.1.5, Section B, subsections (6) and (7) of this ordinance are met.
- (i) A description of proposed watercourse alteration or relocation, when applicable, including an engineering report on the effects of the proposed project on the flood-carrying capacity of the watercourse and the effects to properties located both upstream and downstream; and a map (if not shown on plot plan) showing the location of the proposed watercourse alteration or relocation.\

(b) Permit Requirements

The Floodplain Development Permit shall include, but not be limited to:

- (a) ~~A description of the development to be permitted under the floodplain development permit.~~

A complete description of all the development to be permitted under the floodplain development permit (e.g. house, garage, pool, septic, bulkhead, cabana, pier, bridge, mining, dredging, filling, grading, paving, excavation or drilling operations, or storage of equipment or materials, etc.).

- (b) The Special Flood Hazard Area determination for the proposed development in accordance with available data specified in Article 7.1.3, Section B.
- (c) The Regulatory Flood Protection Elevation required for the reference level and all attendant utilities.
- (d) The Regulatory Flood Protection Elevation required for the protection of all public utilities.
- (e) All certification submittal requirements with timelines.
- (f) ~~A statement that no fill material or other development shall encroach into the floodway or non-encroachment area of any watercourse, as applicable.~~

A statement that no fill material or other development shall encroach into the floodway or non-encroachment area of any watercourse unless the requirements of Article 7.1.5, Section F have been met.
- (g) The flood openings requirements, if in Zones A, AE.
- (h) Limitations of below BFE enclosure uses (if applicable). (i.e., parking, building access and limited storage only).
- (i) A statement, if in Zone VE, that there shall be no alteration of sand dunes which would increase potential flood damage.
- (j) A statement, if in Zone VE, that there shall be no fill used for structural support.
- (k) A statement, that all materials below BFE/RFPE must be flood resistant materials.

(c) Certification Requirements

- (a) Elevation Certificates

- (a) An Elevation Certificate (FEMA Form 086-0-33) is required prior to the actual start of any new construction. It shall be the duty of the permit holder to submit to the Floodplain Administrator a certification of the elevation of the reference level, in relation to NAVD 1988. The Floodplain Administrator shall review the certificate data submitted. Deficiencies detected by such review shall be corrected by the permit holder prior to the beginning of construction. Failure to submit the certification or failure to make required corrections shall be cause to deny a floodplain development permit.
- (b) An elevation certificate (FEMA Form 086-0-33) is required after the reference level is established. Within seven (7) calendar days of establishment of the reference level elevation, it shall be the duty of the permit holder to submit to the Floodplain Administrator a certification of the elevation of the reference level in relation to NAVD 1988. Any work done within the seven (7) day calendar period and prior to submission of the certification shall be at the permit holder's risk. The Floodplain Administrator shall review the certificate data submitted. Deficiencies detected by such review shall be corrected by the permit holder immediately and prior to further work being permitted to proceed. Failure to submit the certification or failure to make required corrections shall be cause to issue a stop-work order for the project.
- (c) A final Finished Construction Elevation Certificate (FEMA Form 086-0-33) is required after construction is completed and prior to Certificate of Compliance/Occupancy issuance. It shall be the duty of the permit holder to submit to the Floodplain Administrator a certification of final as-built construction of the elevation of the reference level and all attendant utilities. The Floodplain Administrator shall review the certificate data submitted. Deficiencies detected by such review shall be corrected by the permit holder immediately and prior to Certificate of Compliance/Occupancy issuance. In some instances, another certification may be required to certify corrected as-built construction. Failure to submit the certification or failure to make required corrections shall be cause to withhold the issuance of a Certificate of Compliance/Occupancy. The Finished Construction Elevation Certificate certifier shall provide at least 2 photographs showing the front and rear of the building taken within 90 days from the date of certification. The photographs must be taken with views confirming the building description and diagram number and provided in Section A. To the extent possible, these photographs should show the entire building including foundation. If the building has split-level areas, provide at least 2 additional photographs showing side views of the building. In addition, when applicable, provide a photograph of the foundation showing a representative example of the flood openings or vents. All photographs must be in color and measure at least 3" x 3". Digital photographs are acceptable.

(b) Floodproofing Certificate

- i. If non-residential floodproofing is used to meet the Regulatory Flood Protection Elevation requirements, a Floodproofing Certificate (FEMA Form 086-0-34), with supporting data, an operational plan, and an inspection and maintenance plan are required prior to the actual start of any new construction. It shall be the duty of the permit holder to submit to the Floodplain Administrator a certification of the floodproofed design elevation of the reference level and all attendant utilities, in relation to NAVD 1988. Floodproofing certification shall be prepared by or under the direct supervision of a professional engineer or architect and certified by same. The Floodplain Administrator shall review the certificate data, the operational plan, and June 2017 NC Model Flood Damage Prevention Ordinance Coastal Summary of Changes 14 the inspection and maintenance plan. Deficiencies detected by such review shall be corrected by the applicant prior to permit approval. Failure to submit the certification or failure to make required corrections shall be cause to deny a Floodplain Development Permit. Failure to construct in accordance

with the certified design shall be cause to withhold the issuance of a Certificate of Compliance/Occupancy.

- ii. A final Finished Construction Floodproofing Certificate (FEMA Form 086-0-34), with supporting data, an operational plan, and an inspection and maintenance plan are required prior to the issuance of a Certificate of Compliance/Occupancy. It shall be the duty of the permit holder to submit to the Floodplain Administrator a certification of the floodproofed design elevation of the reference level and all attendant utilities, in relation to NAVD 1988. Floodproofing certificate shall be prepared by or under the direct supervision of a professional engineer or architect and certified by same. The Floodplain Administrator shall review the certificate data, the operational plan and the inspection and maintenance plan. Deficiencies detected by such review shall be corrected by the applicant prior to Certificate of Occupancy. Failure to submit the certification or failure to make required corrections shall be cause to deny a Floodplain Development Permit. Failure to construct in accordance with the certified design shall be cause to deny a Certificate of Compliance/Occupancy.

- (c) If a manufactured home is placed within Zones A or AE and the elevation of the chassis is more than 36 inches in height above grade, an engineered foundation certification is required in accordance with the provisions of Article 7.1.5, Section B(3)(b).
- (d) If a watercourse is to be altered or relocated, a description of the extent of watercourse alteration or relocation; a professional engineer's certified report on the effects of the proposed project on the flood-carrying capacity of the watercourse and the effects to properties located both upstream and downstream; and a map showing the location of the proposed watercourse alteration or relocation shall all be submitted by the permit applicant prior to issuance of a floodplain development permit.
- (e) Certification Exemptions: The following structures, if located within Zones A or AE are exempt from the elevation/floodproofing certification requirements specified in items (a) and (b) of this subsection:
 - i. Recreational Vehicles meeting requirements of Article 5, Section B(6)(a);
 - ii. Temporary Structures meeting requirements of Article 5, Section B(7); and
 - iii. Accessory Structures that are 150 square feet or less or \$3,000 or less and meeting requirements of Article 7.1.5, Section B(8)
- (f) A V-Zone Certification with accompanying design plans and specifications is required prior to issuance of a Floodplain Development Permit within coastal high hazard areas. It shall be the duty of the permit applicant to submit to the Floodplain Administrator said certification to ensure the design standards of this ordinance are met. A registered professional engineer or architect shall develop or review the structural design, plans, and specifications for construction and certify that the design and methods of construction to be used are in accordance with accepted standards of practice for meeting the provisions of this ordinance. This certification is not a substitute for an elevation certificate. In addition, prior to the Certificate of Compliance/Occupancy issuance, a registered professional engineer or architect shall certify the finished construction is compliant with the design, specifications, and plans for VE Zone construction.

(d) Determinations for Existing Buildings and Structures

For applications for building permits to improve buildings and structures, including alterations, movement, enlargement, replacement, repair, change of occupancy, additions, rehabilitations, renovations, substantial improvements, repairs of substantial damage, and any other improvement of or work on such buildings and structures, the Floodplain Administrator, in coordination with the Building Official, shall:

- (a) Estimate the market value, or require the applicant to obtain an appraisal of the market value prepared by a qualified independent appraiser, of the building or structure before the start of construction of

the proposed work; in the case of repair, the market value of the building or structure shall be the market value before the damage occurred and before any repairs are made;

- (b) Compare the cost to perform the improvement, the cost to repair a damaged building to its pre-damaged condition, or the combined costs of improvements and repairs, if applicable, to the market value of the building or structure;
- (c) Determine and document whether the proposed work constitutes substantial improvement or repair of substantial damage; and
- (d) Notify the applicant if it is determined that the work constitutes substantial improvement or repair of substantial damage and that compliance with the flood resistant construction requirements of the NC Building Code and this ordinance is required.

C. Duties and Responsibilities of the Floodplain Administrator

The Floodplain Administrator shall perform, but not be limited to, the following duties:

- (1) Review all floodplain development applications and issue permits for all proposed development within Special Flood Hazard Areas to assure that the requirements of this ordinance have been satisfied.
- (2) Review all proposed development within Special Flood Hazard Areas to assure that all necessary local, state and federal permits have been received, including Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334.
- (3) Notify adjacent communities and the North Carolina Department of Public Safety, Division of Emergency Management, State Coordinator for the National Flood Insurance Program prior to any alteration or relocation of a watercourse, and submit evidence of such notification to the Federal Emergency Management Agency (FEMA).
- (4) Assure that maintenance is provided within the altered or relocated portion of said watercourse so that the flood-carrying capacity is maintained.
- (5) Prevent encroachments into floodways and non-encroachment areas unless the certification and flood hazard reduction provisions of Article 7.1.5, Section F are met.
- (6) Obtain actual elevation (in relation to NAVD 1988) of the reference level (including basement) and all attendant utilities of all new and substantially improved structures, in accordance with the provisions of Article 7.1.4, Section B(3).
- (7) Obtain actual elevation (in relation to NAVD 1988) to which all new and substantially improved structures and utilities have been floodproofed, in accordance with the provisions of Article 7.1.4, Section B(3).
- (8) Obtain actual elevation (in relation to NAVD 1988) of all public utilities in accordance with the provisions of Article 7.1.4, Section B(3).
- (9) When floodproofing is utilized for a particular structure, obtain certifications from a registered professional engineer or architect in accordance with the provisions of Article 7.1.4, Section B(3) and Article 7.1.5, Section B(2).
- (10) Where interpretation is needed as to the exact location of boundaries of the Special Flood Hazard Areas, floodways, or non-encroachment areas (for example, where there appears to be a conflict between a mapped boundary and actual field conditions), make the necessary interpretation. The person contesting the location of the boundary shall be given a reasonable opportunity to appeal the interpretation as provided in this section.

(11) When BFE data has not been provided in accordance with the provisions of Article 7.1.3, Section B, obtain, review, and reasonably utilize any BFE data, along with floodway data or non-encroachment area data available from a federal, state, or other source, including data developed pursuant to Article 7.1.5, Section D(2)(c), in order to administer the provisions of this ordinance.

(12) When BFE data is provided but no floodway or non-encroachment area data has been provided in accordance with the provisions of Article 7.1.3, Section B, obtain, review, and reasonably utilize any floodway data or non-encroachment area data available from a federal, state, or other source in order to administer the provisions of this ordinance.

(13) When the lowest ground elevation of a parcel or structure in a Special Flood Hazard Area is above the Base Flood Elevation, advise the property owner of the option to apply for a Letter of Map Amendment (LOMA) from FEMA. Maintain a copy of the Letter of Map Amendment (LOMA) issued by FEMA in the floodplain development permit file.

When the lowest floor and the lowest adjacent grade of a structure or the lowest ground elevation of a parcel in a Special Flood Hazard Area is above the BFE, advise the property owner of the option to apply for a Letter of Map Amendment (LOMA) from FEMA. Maintain a copy of the LOMA issued by FEMA in the floodplain development permit file.

(14) Permanently maintain all records that pertain to the administration of this ordinance and make these records available for public inspection, recognizing that such information may be subject to the Privacy Act of 1974, as amended.

(15) Make on-site inspections of work in progress. As the work pursuant to a floodplain development permit progresses, the Floodplain Administrator shall make as many inspections of the work as may be necessary to ensure that the work is being done according to the provisions of the local ordinance and the terms of the permit. In exercising this power, the Floodplain Administrator has a right, upon presentation of proper credentials, to enter on any premises within the jurisdiction of the community at any reasonable hour for the purposes of inspection or other enforcement action.

(16) Issue stop-work orders as required. Whenever a building or part thereof is being constructed, reconstructed, altered, or repaired in violation of this ordinance, the Floodplain Administrator may order the work to be immediately stopped. The stop-work order shall be in writing and directed to the person doing or in charge of the work. The stop-work order shall state the specific work to be stopped, the specific reason(s) for the stoppage, and the condition(s) under which the work may be resumed. Violation of a stop-work order constitutes a misdemeanor.

(17) Revoke floodplain development permits as required. The Floodplain Administrator may revoke and require the return of the floodplain development permit by notifying the permit holder in writing stating the reason(s) for the revocation. Permits shall be revoked for any substantial departure from the approved application, plans, and specifications; for refusal or failure to comply with the requirements of State or local laws; or for false statements or misrepresentations made in securing the permit. Any floodplain development permit mistakenly issued in violation of an applicable State or local law may also be revoked.

(18) Make periodic inspections throughout the Special Flood Hazard Areas within the jurisdiction of the community. The Floodplain Administrator and each member of his or her inspections department shall have a right, upon presentation of proper credentials, to enter on any premises within the territorial jurisdiction of the department at any reasonable hour for the purposes of inspection or other enforcement action.

(19) Follow through with corrective procedures of Article 7.1.4, Section D.

(20) Review, provide input, and make recommendations for variance requests.

- (21) ~~Maintain a current map repository to include, but not limited to, the FIS Report, FIRM and other official flood maps and studies adopted in accordance with Section 7.1.3.B of this Ordinance, including any revisions thereto including Letters of Map Change, issued by FEMA. Notify State and FEMA of mapping needs.~~

Maintain a current map repository to include, but not limited to, historical and effective FIS Report, historical and effective FIRM and other official flood maps and studies adopted in accordance with the provisions of Article 7.1.3, Section B of this ordinance, including any revisions thereto including Letters of Map Change, issued by FEMA. Notify State and FEMA of mapping needs.

- (22) Coordinate revisions to FIS reports and FIRMs, including Letters of Map Revision Based on Fill (LOMR-Fs) and Letters of Map Revision (LOMRs).

D. Corrective Procedures

(1) **Violations to be Corrected**

When the Floodplain Administrator finds violations of applicable state and local laws; it shall be his or her duty to notify the owner or occupant of the building of the violation. The owner or occupant shall immediately remedy each of the violations of law cited in such notification.

(2) **Actions in Event of Failure to Take Corrective Action:**

~~If the owner of a building or property shall fail to take prompt corrective action, the floodplain administrator shall give the owner written notice, by certified or registered mail to the owner's last known address or by personal service, stating:~~

If the owner of a building or property shall fail to take prompt corrective action, the Floodplain Administrator shall give the owner written notice, by certified or registered mail to the ~~June 2017 NC Model Flood Damage Prevention Ordinance Coastal Summary of Changes 17~~ owner's last known address or by personal service, stating: **THE PREVIOUS STATEMENT NEEDS CORRECTING AS INDICATED**

- (a) That the building or property is in violation of the floodplain management regulations;
- (b) That a hearing will be held before the Floodplain Administrator at a designated place and time, not later than ten (10) days after the date of the notice, at which time the owner shall be entitled to be heard in person or by counsel and to present arguments and evidence pertaining to the matter; and
- (c) That following the hearing, the Floodplain Administrator may issue an order to alter, vacate, or demolish the building; or to remove fill as applicable.

(3) **Order to Take Corrective Action:**

If, upon a hearing held pursuant to the notice prescribed above, the Floodplain Administrator shall find that the building or development is in violation of the Flood Damage Prevention Ordinance, he or she shall issue an order in writing to the owner, requiring the owner to remedy the violation within a specified time period, not less than sixty (60) calendar days, nor more than least Insert Calendar Days (One-hundred-eighty (180) calendar days or less is recommended) calendar days. Where the Floodplain Administrator finds that there is imminent danger to life or other property, he or she may order that corrective action be taken in such lesser period as may be feasible.

(4) **Appeal:**

Any owner who has received an order to take corrective action may appeal the order to the local elected governing body by giving notice of appeal in writing to the Floodplain Administrator and the clerk within

ten (10) days following issuance of the final order. In the absence of an appeal, the order of the Floodplain Administrator shall be final. The local governing body shall hear an appeal within a reasonable time and may affirm, modify and affirm, or revoke the order.

(5) **Failure to Comply with Order:**

~~If the owner of a building or property fails to comply with an order to take corrective action for which no appeal has been made or fails to comply with an order of the governing body following an appeal, the owner shall be guilty of a misdemeanor and shall be punished at the discretion of the court.~~

If the owner of a building or property fails to comply with an order to take corrective action for which no appeal has been made or fails to comply with an order of the governing body following an appeal, the owner shall be guilty of a Class 1 misdemeanor pursuant to NC G.S. § 143-215.58 and shall be punished at the discretion of the court.

E. Variance Procedures

- (1) The Board of Adjustment, as established by the County of Brunswick, hereinafter referred to as the "appeal board", shall hear and decide requests for variances from the requirements of this Ordinance.
- (2) Any person aggrieved by the decision of the appeal board may appeal such decision to the Court, as provided in Chapter 7A of the North Carolina General Statutes.
- (3) Variances may be issued for:
 - (a) The repair or rehabilitation of historic structures upon the determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and that the variance is the minimum necessary to preserve the historic character and design of the structure;
 - (b) Functionally dependent facilities if determined to meet the definition as stated in Article 7.1.2 of this ordinance, provided provisions of Article 7.1.4, Section E(9)(b), (c), and (e) have been satisfied, and such facilities are protected by methods that minimize flood damages during the base flood and create no additional threats to public safety; or
 - (c) Any other type of development provided it meets the requirements of this Section.
- (4) ~~All new construction and substantial improvements shall be designed (or modified) and adequately anchored to prevent flotation, collapse, and lateral movement of the structure.~~ **WRONG SEC...MOVE TO ART 5**
In passing upon variances, the appeal board shall consider all technical evaluations, all relevant factors, all standards specified in other sections of this ordinance, and:
 - (a) The danger that materials may be swept onto other lands to the injury of others;
 - (b) The danger to life and property due to flooding or erosion damage.
 - (c) The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner;
 - (d) The importance of the services provided by the proposed facility to the community;
 - (e) The necessity to the facility of a waterfront location as defined under Article 7.1.2 of this ordinance as a functionally dependent facility, where applicable;

- (f) The availability of alternative locations, not subject to flooding or erosion damage, for the proposed use;
 - (g) The compatibility of the proposed use with existing and anticipated development;
 - (h) The relationship of the proposed use to the comprehensive plan and floodplain management program for that area;
 - (i) The safety of access to the property in times of flood for ordinary and emergency vehicles;
 - (j) The expected heights, velocity, duration, rate of rise, and sediment transport of the floodwaters and the effects of wave action, if applicable, expected at the site; and
 - (k) The costs of providing governmental services during and after flood conditions including maintenance and repair of public utilities and facilities such as sewer, gas, electrical and water systems, and streets and bridges.
- (5) A written report addressing each of the above factors shall be submitted with the application for a variance.
- (6) Upon consideration of the factors listed above and the purposes of this ordinance, the appeal board may attach such conditions to the granting of variances as it deems necessary to further the purposes and objectives of this ordinance.
- (7) Any applicant to whom a variance is granted shall be given written notice specifying the difference between the BFE and the elevation to which the structure is to be built and that such construction below the BFE increases risks to life and property, and that the issuance of a variance to construct a structure below the BFE may result in increased premium rates for flood insurance up to \$25 per \$100 of insurance coverage. Such notification shall be maintained with a record of all variance actions, including justification for their issuance.
- (8) The Floodplain Administrator shall maintain the records of all appeal actions and report any variances to the FEMA and the State of North Carolina upon request.
- (9) Conditions for Variances:
- (a) Variances shall not be issued when the variance will make the structure in violation of other federal, state, or local laws, regulations, or ordinances.
 - (b) Variances shall not be issued within any designated floodway or non-encroachment area if the variance would result in any increase in flood levels during the base flood discharge.
 - (c) Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
 - (d) Variances shall only be issued prior to development permit approval.
 - (e) Variances shall only be issued upon:
 - i. A showing of good and sufficient cause;
 - ii. A determination that failure to grant the variance would result in exceptional hardship; and

- iii. A determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, or extraordinary public expense, create nuisance, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
- (10) A variance may be issued for solid waste disposal facilities, hazardous waste management facilities, salvage yards, and chemical storage facilities that are located in Special Flood Hazard Areas provided that all of the following conditions are met.
- (a) The use serves a critical need in the community.
 - (b) No feasible location exists for the use outside the Special Flood Hazard Area.
 - (c) The reference level of any structure is elevated or floodproofed to at least the Regulatory Flood Protection Elevation.
 - (d) The use complies with all other applicable federal, state and local laws.
 - (e) **The Community Name** Brunswick County has notified the Secretary of the North Carolina Department of Public Safety of its intention to grant a variance at least thirty (30) calendar days prior to granting the variance.

7.1.5. Provisions for Flood Hazard Reduction

A. General Standards

In all Special Flood Hazard Areas the following provisions are required:

- (1) All new construction and substantial improvements shall be designed (or modified) and adequately anchored to prevent flotation, collapse, and lateral movement of the structure.
- (2) ~~All new construction and substantial improvements shall be constructed with materials and utility equipment resistant to flood damage.~~

All new construction and substantial improvements shall be constructed with materials and utility equipment resistant to flood damage in accordance with the FEMA Technical Bulletin 2, Flood Damage-Resistant Materials Requirements.

- (3) All new construction and substantial improvements shall be constructed by methods and practices that minimize flood damages.
- (4) ~~Electrical, heating, ventilation, plumbing, air conditioning equipment, and other service facilities shall be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding. These include, but are not limited to, HVAC equipment, water softener units, bath/kitchen fixtures, ductwork, electric/gas meter panels/boxes, utility/cable boxes, appliances (washers, dryers, refrigerators, freezers, etc.), hot water heaters, and electric outlets/switches.~~

All new electrical, heating, ventilation, plumbing, air conditioning equipment, and other service equipment shall be located at or above the RFPE or designed and installed to prevent water from entering or accumulating within the components during the occurrence of the base flood. These include, but are not limited to, HVAC equipment, water softener units, bath/kitchen fixtures, ductwork, electric/gas meter panels/boxes, utility/cable boxes, water heaters, and electric outlets/switches.

- (a) Replacements part of a substantial improvement, electrical, heating, ventilation, plumbing, air conditioning equipment, and other service equipment shall also meet the above provisions.
 - (b) Replacements that are for maintenance and not part of a substantial improvement, may be installed at the original location provided the addition and/or improvements only comply with the standards for new construction consistent with the code and requirements for the original structure.
- (5) All new and replacement water supply systems shall be designed to minimize or eliminate infiltration of floodwaters into the system.
- (6) New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of floodwaters into the systems and discharges from the systems into flood waters.
- (7) On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding.
- (8) ~~Any alteration, repair, reconstruction, or improvements to a structure, which is in compliance with the provisions of this Ordinance, shall meet the requirements of "new construction" as contained in this Ordinance.~~ DELETED
- (8) Nothing in this ordinance shall prevent the repair, reconstruction, or replacement of a building or structure existing on the effective date of this ordinance and located totally or partially within the floodway, non-encroachment area, or stream setback, provided there is no additional encroachment below the Regulatory Flood Protection Elevation in the floodway, non-encroachment area, or stream setback, and provided that such repair, reconstruction, or replacement meets all of the other requirements of this ordinance.
- (9) New solid waste disposal facilities and sites, hazardous waste management facilities, salvage yards, and chemical storage facilities shall not be permitted, except by variance as specified in Article 7.1.4, Section E (10). A structure or tank for chemical or fuel storage incidental to an allowed use or to the operation of a water treatment plant or wastewater treatment facility may be located in a Special Flood Hazard Area only if the structure or tank is either elevated or floodproofed to at least the Regulatory Flood Protection Elevation and certified in accordance with the provisions of Article 7.1.4, Section B (3).
- (10) All subdivision proposals and other development proposals shall be consistent with the need to minimize flood damage.
- (11) All subdivision proposals and other development proposals shall have public utilities and facilities such as sewer, gas, electrical, and water systems located and constructed to minimize flood damage.
- (12) All subdivision proposals and other development proposals shall have adequate drainage provided to reduce exposure to flood hazards.
- (13) All subdivision proposals and other development proposals shall have received all necessary permits from those governmental agencies for which approval is required by federal or state law, including Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334.

- (14) When a structure is partially located in a Special Flood Hazard Area, the entire structure shall meet the requirements for new construction and substantial improvements.
- (15) When a structure is located in multiple flood hazard zones or in a flood hazard risk zone with multiple base flood elevations, the provisions for the more restrictive flood hazard risk zone and the highest BFE shall apply.

B. Specific Standards

In all Special Flood Hazard Areas where Base Flood Elevation (BFE) data has been provided, as set forth in Article 7.1.3. Section B, or Article 7.1.5. Section D, the following provisions, in addition to Section 7.1.5.A, are required:

(1) Residential Construction

~~New construction and substantial improvement of any residential structure (including mobile homes) shall have the reference level, including basement, elevated two feet above base flood elevation, as defined in [Article 2](#) of this Ordinance.~~

New construction and substantial improvement of any residential structure (including manufactured homes) shall have the reference level, including basement, elevated no lower than the Regulatory Flood Protection Elevation, as defined in Article 7.1.2 of this ordinance.

(2) Non-Residential Construction

~~New construction and substantial improvement of any commercial, industrial, or other non-residential structure shall have the reference level, including basement, elevated no lower than the regulatory flood protection elevation, as defined in Section 7.1.2. Structures located in A, AE and A1-30 Zones may be floodproofed to the regulatory flood protection elevation in lieu of elevation provided that all areas of the structure, together with attendant utility and sanitary facilities, below the regulatory flood protection elevation are watertight with walls substantially impermeable to the passage of water, using structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. For AO Zones, the floodproofing elevation shall be in accordance with Section 7.1.5.H.3. A registered professional engineer or architect shall certify that the standards of this subsection are satisfied. Such certification shall be provided to the Floodplain Administrator as set forth in Section 7.1.4.B.3, along with the operational and maintenance plans.~~

New construction and substantial improvement of any commercial, industrial, or other non-residential structure shall have the reference level, including basement, elevated no lower than the Regulatory Flood Protection Elevation, as defined in Article 7.1.2 of this ordinance. Structures located in Zones A, AE, AH, AO, A99 may be floodproofed to the Regulatory Flood Protection Elevation in lieu of elevation provided that all areas of the structure, together with attendant utility and sanitary facilities, below the Regulatory Flood Protection Elevation are watertight with walls substantially impermeable to the passage of water, using structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. A registered professional engineer or architect shall certify that the floodproofing standards of this subsection are satisfied. Such certification shall be provided to the Floodplain Administrator as set forth in Article 7.1.4, Section B (3), along with the operational plan and the inspection and maintenance.

(3) Mobile Homes Manufactured Homes

- (a) ~~New or replacement mobile homes shall be elevated so that the reference level of the mobile home is two feet above base flood elevation, as defined in Section 7.1.2.~~

New and replacement manufactured homes shall be elevated so that the reference level of the manufactured home is no lower than the Regulatory Flood Protection Elevation, as defined in Article 7.1.2 of this ordinance.

- (b) ~~Mobile homes shall be securely anchored to an adequately anchored foundation to resist flotation, collapse, and lateral movement, either by engineer certification, or in accordance with the most current edition of the State of North Carolina Regulations for Mobile Homes, adopted by the Commissioner of Insurance pursuant to G.S. 143-143.15 or a certified engineered foundation. Additionally, when the elevation would be met by an elevation of the chassis 36 inches or less above the grade at the site, the chassis shall be supported by~~

Manufactured homes shall be securely anchored to an adequately anchored foundation to resist flotation, collapse, and lateral movement, either by certified engineered foundation system, or in accordance with the most current edition of the State of North Carolina Regulations for Manufactured Homes adopted by the Commissioner of Insurance pursuant to NCGS 143-143.15. Additionally, when the elevation would be met by an elevation of the chassis thirty-six (36) inches or less above the grade at the site, the chassis shall be supported by reinforced piers or engineered foundation. When the elevation of the chassis is above thirty-six (36) inches in height, an engineering certification is required.

- (c) ~~Reinforced piers or engineered foundation. When the elevation of the chassis is above 36 inches in height, an engineering certification is required.~~
- (c) All enclosures or skirting below the lowest floor shall meet the requirements of Article 7.1.5. Section B (4).
- (d) An evacuation plan must be developed for evacuation of all residents of all new, substantially improved or substantially damaged mobile home parks or subdivisions located within flood prone areas. This plan shall be filed with and approved by the floodplain administrator and the local Emergency Management Coordinator.

(4) Elevated Buildings

~~Fully enclosed areas of new construction and substantially improved structures, which are below the lowest floor:~~

Fully enclosed area, of new construction and substantially improved structures, which is below the lowest floor or below the lowest horizontal structural member in VE zones:

- (a) Shall not be designed or used for human habitation, but shall only be used for parking of vehicles, building access, or limited storage of maintenance equipment used in connection with the premises. Access to the enclosed area shall be the minimum necessary to allow for parking of vehicles (garage door) or limited storage of maintenance equipment (standard exterior door), or entry to the living area (stairway or elevator). The interior portion of such enclosed area shall not be finished or partitioned into separate rooms, except to enclose storage areas;
- (b) Shall be constructed entirely of flood resistant materials, up to the Regulatory Flood Protection Elevation and
- (c) Shall include, in Zones A, ~~AO~~, AE, and **A1-30**, flood openings to automatically equalize hydrostatic flood forces on walls by allowing for the entry and exit of floodwaters. To meet this requirement,

the openings must either be certified by a professional engineer or architect or meet or exceed the following minimum design criteria:

- i. A minimum of two flood openings on different sides of each enclosed area subject to flooding;
 - ii. The total net area of all flood openings must be at least one (1) square inch for each square foot of enclosed area subject to flooding;
 - iii. If a building has more than one enclosed area, each enclosed area must have flood openings to allow floodwaters to automatically enter and exit;
 - iv. The bottom of all required flood openings shall be no higher than one (1) foot above the higher of the interior or exterior adjacent grade;
 - v. Flood openings may be equipped with screens, louvers, or other coverings or devices, provided they permit the automatic flow of floodwaters in both directions; and
 - vi. Enclosures made of flexible skirting are not considered enclosures for regulatory purposes, and, therefore, do not require flood openings. Masonry or wood underpinning, regardless of structural status, is considered an enclosure and requires flood openings as outlined above.
- (d) Shall allow, in Coastal High Hazard Areas (Zones VE and V1-30), **either be free of obstruction or constructed with** breakaway walls, open wood latticework or insect screening, provided **they are** not part of the structural support of the building and is designed so as to breakaway, under abnormally high tides or wave action, without causing damage to the **elevated portion of the building or supporting foundation system or otherwise jeopardizing the** structural integrity of the building, provided the following design specifications are met: **The following design specifications shall be met:**
- i. ~~Material shall consist of open wood latticework or insect screening; or~~
Material shall consist of open wood or plastic lattice, or insect screening; or
 - ii. Breakaway walls shall meet the following design specifications:
 - ~~(1) Breakaway walls shall have flood openings that allow for the automatic entry and exit of floodwaters to minimize damage caused by hydrostatic loads, per Article 7.1.5, Section B(4)(d)(i-vi); (OPTIONAL) and~~
 - (1) Design safe loading resistance of each wall shall be not less than 10 nor more than 20 pounds per square foot; or
 - (2) Breakaway walls that exceed a design safe loading resistance of 20 pounds per square foot (either by design or when so required by State or local codes) shall be certified by a registered professional engineer or architect that the breakaway wall will collapse from a water load less than that which would occur during the base flood event, and the elevated portion of the building and supporting foundation system shall not be subject to collapse, displacement, or other structural damage due to the effects of wind and water loads acting simultaneously on all building components (structural and nonstructural). The water loading values used shall be those associated with the base flood. The wind loading values used shall be those required by the North Carolina State Building Code.

- iii. Concrete pads, including patios, decks, parking pads, walkways, driveways, pool decks, etc. the following is required: **(OPTIONAL)**
 - (1) Shall be structurally independent of the primary structural foundation system of the structure and shall not adversely affect structures through redirection of floodwaters or debris; and
 - (2) Shall be constructed to breakaway cleanly during design flood conditions, shall be frangible, and shall not produce debris capable of causing damage to any structure. (The installation of concrete in small segments (approximately 4 feet x 4 feet) that will easily break up during the base flood event, or score concrete in 4 feet x 4 feet maximum segments is acceptable to meet this standard); and
 - (3) Reinforcing, including welded wire fabric, shall not be used in order to minimize the potential for concreted pads being a source of debris; and
 - (4) Pad thickness shall not exceed 4 inches; or
 - (5) Provide a Design Professional's certification stating the design and method of construction to be used meet the applicable criteria of this section.

(e) Fill/Grading

- i. Minor grading and the placement of minor quantities of nonstructural fill may be permitted for landscaping and for drainage purposes under and around buildings and for support of parking slabs, pool decks, patios and walkways.
 - ii. The fill material must be similar and consistent with the natural soils in the area.
 - iii. The placement of site-compatible, non-structural fill under or around an elevated building is limited to two (2) feet. Fill greater than two (2) feet must include an analysis prepared by a qualified registered design professional demonstrating no harmful diversion of floodwaters or wave runup and wave reflection that would increase damage to adjacent elevated buildings and structures.
 - iv. Nonstructural fill with finished slopes that are steeper than five (5) units horizontal to one (1) unit vertical shall be permitted only if an analysis prepared by a qualified registered design professional demonstrates no harmful diversion of floodwaters or wave runup and wave reflection that would increase damage to adjacent elevated buildings and structures.
- (f) ~~Property owners shall be required to execute and record a non-conversion agreement prior to issuance of a building permit declaring that the area below the lowest floor shall not be improved, finished or otherwise converted to habitable space; Brunswick County will have the right to inspect the enclosed area. This agreement shall be recorded with the Brunswick County Register of Deeds and shall transfer with the property in perpetuity.~~
- (g) ~~Release of restrictive covenant. If a property which is bound by a non-conversion agreement is modified to remove enclosed areas below BFE, then the owner may request release of restrictive covenant after staff inspection and submittal of confirming documentation.~~

(5) Additions / Improvements

(a) Additions and/or improvements to pre-FIRM structures when the addition and/or improvements in combination with any interior modifications to the existing structure are:

- i. Not a substantial improvement, the addition and/or improvements must be designed to minimize flood damages and must not be any more non-conforming than the existing structure.
- ii. ~~A substantial improvement, both the existing structure and the addition and/or improvements must comply with the standards for new construction.~~

A substantial improvement, with modifications/rehabilitations/improvements to the existing structure or the common wall is structurally modified more than installing a doorway, both the existing structure and the addition must comply with the standards for new construction.

~~(b) Additions to post-FIRM structures with no modifications to the existing structure other than a standard door in the common wall shall require only the addition to comply with the standards for new construction.~~

Additions to pre-FIRM or post-FIRM structures that are a substantial improvement with no modifications/rehabilitations/improvements to the existing structure other than a standard door in the common wall, shall require only the addition to comply with the standards for new construction.

(c) Additions and/or improvements to post-FIRM structures when the addition and/or improvements in combination with any interior modifications to the existing structure are:

- i. ~~Not a substantial improvement, the addition and/or improvements only must comply with the standards for new construction.~~

Not a substantial improvement, the addition and/or improvements only must comply with the standards for new construction consistent with the code and requirements for the original structure.

- ii. A substantial improvement, both the existing structure and the addition and/or improvements must comply with the standards for new construction.

(d) Any combination of repair, reconstruction, rehabilitation, addition or improvement of a building or structure taking place during a **One (1) year period**, the cumulative cost of which equals or exceeds 50 percent of the market value of the structure before the improvement or repair is started must comply with the standards for new construction. For each building or structure, **the One (1) year period** begins on the date of the first improvement or repair of that building or structure subsequent to the effective date of this ordinance. Substantial damage also means flood related damage sustained by a structure on two separate occasions during a 10-year period for which the cost of repairs at the time of each such flood event, on the average, equals or exceeds 25 percent of the market value of the structure before the damage occurred. If the structure has sustained substantial damage, any repairs are considered substantial improvement regardless of the actual repair work performed. The requirement does not, however, include either:

- (a) Any project for improvement of a building required to correct existing health, sanitary or safety code violations identified by the building official and that are the minimum necessary to assume safe living conditions.
- (b) Any alteration of a historic structure provided that the alteration will not preclude the structure's continued designation as a historic structure.

(6) Recreational Vehicles

Recreational vehicles shall either:

(a) Temporary Placement

- i. ~~Be on site for fewer than 180 consecutive days and be fully licensed and ready for highway use (a recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities, and has no permanently attached additions); or~~

Be on site for fewer than 180 consecutive days; ~~or~~ and

- ii. ~~Meet all the requirements for new construction.~~

Be fully licensed and ready for highway use. (A recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities, and has no permanently attached additions.)

- (b) Permanent Placement. Recreational vehicles that do not meet the limitations of Temporary Placement shall meet all the requirements for new construction.

(7) Temporary Non-Residential Structures

Prior to the issuance of a floodplain development permit for a temporary structure, the applicant must submit to the Floodplain Administrator a plan for the removal of such structure(s) in the event of a hurricane, flash flood or other type of flood warning notification. The following information shall be submitted in writing to the Floodplain Administrator for review and written approval:

- (a) A specified time period for which the temporary use will be permitted. Time specified may not exceed three (3) months, renewable up to one (1) year;
- (b) The name, address, and phone number of the individual responsible for the removal of the temporary structure;
- (c) The time frame prior to the event at which a structure will be removed (i.e., minimum of 72 hours before landfall of a hurricane or immediately upon flood warning notification);
- (d) A copy of the contract or other suitable instrument with the entity responsible for physical removal of the structure; and
- (e) Designation, accompanied by documentation, of a location outside the Special Flood Hazard Area, to which the temporary structure will be moved.

(8) Accessory Structures

When accessory structures (sheds, detached garages, etc.) are to be placed within a Special Flood Hazard Area, the following criteria shall be met:

- (a) Accessory structures shall not be used for human habitation (including working, sleeping, living, cooking or restroom areas);
- (b) Accessory structures shall not be temperature-controlled;
- (c) Accessory structures shall be designed to have low flood damage potential;
- (d) Accessory structures shall be constructed and placed on the building site so as to offer the minimum resistance to the flow of floodwaters;
- (e) Accessory structures shall be firmly anchored in accordance with the provisions of Article 7.1.5, Section A(1);
- (f) All service facilities such as electrical shall be installed in accordance with the provisions of Article 7.1.5, Section A(4); and
- (g) Flood openings to facilitate automatic equalization of hydrostatic flood forces shall be provided below Regulatory Flood Protection Elevation in conformance with the provisions of Article 7.1.5, Section B(4)(c).

~~An accessory structure with a footprint less than 150 square feet that satisfies the criteria outlined above does not require an elevation or floodproofing certificate. Elevation or floodproofing certifications are required for all other accessory structures in accordance with Section 7.1.4.B.3.~~

An accessory structure with a footprint less than (150 sq ft) or that is a minimal investment of (\$3,000) or less and satisfies the criteria outlined above is not required to meet the elevation or floodproofing standards of Article 7.1.5, Section B (2). Elevation or floodproofing certifications are required for all other accessory structures in accordance with Article 7.1.4, Section B (3).

9. Tanks

- (a) Underground tanks

Underground tanks in flood hazard areas shall be anchored to prevent flotation, collapse or lateral movement resulting from hydrodynamic and hydrostatic loads during conditions of the design flood, including the effects of buoyancy assuming the tank is empty.

- (b) Above-ground tanks, elevated

Above ground tanks in flood hazard areas shall be elevated to or above the Regulatory Flood Protection Elevation on a supporting structure that is designed to prevent flotation, collapse or lateral movement during conditions of the design flood. Tank-supporting structures shall meet the foundation requirements of the applicable flood hazard area;

- (c) Above-ground tanks, not elevated

Above-ground tanks that do not meet the elevation requirements of Article 7.1.5, Section B(2) of this ordinance shall be permitted in flood hazard areas provided the tanks are designed, constructed, installed, and anchored to resist all flood-related and other loads, including the effects of buoyancy, during conditions of the design flood and without release of contents in the floodwaters or

infiltration by floodwaters into the tanks. Tanks shall be designed, constructed, installed and anchored to resist the potential buoyant and other flood forces acting on an empty tank during design flood conditions.

(d) Tank inlets and vents

Tank inlets, fill openings, outlets and vents shall be:

- i. At or above the Regulatory Flood Protection Elevation or fitted with covers designed to prevent the inflow of floodwater or outflow of the contents of the tanks during conditions of the design flood; and
- ii. Anchored to prevent lateral movement resulting from hydrodynamic and hydrostatic Loads, including the effects of buoyancy, during conditions of the design flood.

10. Other Development

- (a) Fences in regulated floodways and NEAs that have the potential to block the passage of floodwaters, such as stockade fences and wire mesh fences, shall meet the limitations of Article 7.1.5, Section F of this ordinance.
- (b) Retaining walls, sidewalks and driveways in regulated floodways and NEAs. Retaining walls and sidewalks and driveways that involve the placement of fill in regulated floodways shall meet the limitations of Article 7.1.5, Section F of this ordinance.
- (c) Roads and watercourse crossings in regulated floodways and NEAs. Roads and watercourse crossings, including roads, bridges, culverts, low-water crossings and similar means for vehicles or pedestrians to travel from one side of a watercourse to the other side, that encroach into regulated floodways shall meet the limitations of Article 7.1.5, Section F of this ordinance.

C. RESERVED

D. Standards for Floodplains Without an Established Base Flood Elevation

~~Within the Special Flood Hazard Areas designated as Approximate Zone A and established in Section 7.1.3.B, where no Base Flood Elevation (BFE) data is available, the following provisions, in addition to Sections 7.1.5.A and 7.1.5.B, shall apply:~~

~~Within the Special Flood Hazard Areas designated as Approximate Zone A and established in Article 7.1.3, Section B, where no BFE data has been provided by FEMA, the following provisions, in addition to the provisions of Article 7.1.5, Section A, shall apply:~~

1. ~~No encroachments, including fill, new construction, substantial improvements or new development shall be permitted within a distance of twenty (20) feet each side from top of bank or five times the width of the stream, whichever is greater, unless certification with supporting technical data by a registered professional engineer is provided demonstrating that such encroachments shall not result in any increase in flood levels during the occurrence of the base flood discharge.~~
2. ~~The BFE used in determining the regulatory flood protection elevation shall be determined based on one of the following criteria set in priority order:~~

~~The BFE used in determining the Regulatory Flood Protection Elevation shall be determined based on the following criteria:~~

- (a) ~~If Base Flood Elevation (BFE) data is available from other sources, all new construction and substantial improvements within such areas shall also comply with all applicable~~

When BFE data is available from other sources, all new construction and substantial improvements within such areas shall also comply with all applicable provisions of this ordinance and shall be elevated or floodproofed in accordance with standards in Article 7.1.5, Sections A and B.

- (b) ~~Provisions of this Ordinance and shall be elevated or floodproofed in accordance with standards in Sections 7.1.4.C (11 and 12).~~

When floodway or non-encroachment data is available from a Federal, State, or other source, all new construction and substantial improvements within floodway and non-encroachment areas shall also comply with the requirements of Article 7.1.5, Sections B and F.

- (c) ~~All subdivision, mobile home park and other development proposals shall provide Base Flood Elevation (BFE) data if development is greater than five acres or has more than 50 lots/mobile home sites. Such Base Flood Elevation (BFE) data shall be adopted by reference per Section 7.1.3.B to be utilized in implementation.~~

All subdivision, manufactured home park and other development proposals shall provide BFE data if development is greater than five (5) acres or has more than fifty (50) lots/manufactured home sites. Such BFE data shall be adopted by reference in accordance with Article 7.1.3, Section B and utilized in implementing this ordinance.

- (d) ~~When Base Flood Elevation (BFE) data is not available from a Federal, State, or other source as outlined above, the reference level shall be elevated to or above the regulatory flood protection elevation, as defined in Section 7.1.2.~~

When BFE data is not available from a Federal, State, or other source as outlined above, the reference level shall be elevated or floodproofed (nonresidential) to or above the Regulatory Flood Protection Elevation, as defined in Article 7.1.2. All other applicable provisions of Article 7.1.5, Section B shall also apply.

E. Standards for Riverine Floodplains with a Base Flood Elevation but Without Established Floodways or Non-Encroachment Areas

~~Along rivers and streams where BFE data is provided but neither floodway nor non-encroachment areas are identified for a Special Flood Hazard Area on the FIRM or in the FIS report, the following requirements shall apply to all development within such areas:~~

Along rivers and streams where BFE data is provided by FEMA or is available from another source but neither floodway nor non-encroachment areas are identified for a Special Flood Hazard Area on the FIRM or in the FIS report, the following requirements shall apply to all development within such areas:

1. Standards of Article 7.1.5, Sections A and B; and
2. Until a regulatory floodway or non-encroachment area is designated, no encroachments, including fill, new construction, substantial improvements, or other development, shall be permitted unless certification with supporting technical data by a registered professional engineer is provided demonstrating that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one (1) foot at any point within the community.

F. Floodways and Non-Encroachment Areas

Areas designated as floodways or non-encroachment areas are located within the Special Flood Hazard Areas established in Article 7.1.3, Section B. The floodways and non-encroachment areas are extremely hazardous areas due to the velocity of floodwaters that have erosion potential and carry debris and potential projectiles. The following provisions, in addition to standards outlined in Article 7.1.5, Sections A and B, shall apply to all development within such areas:

- (1) No encroachments, including fill, new construction, substantial improvements and other developments shall be permitted unless:
 - (a) It is demonstrated that the proposed encroachment would not result in any increase in the flood levels during the occurrence of the base flood discharge, based on hydrologic and hydraulic analyses performed in accordance with standard engineering practice and presented to the Floodplain Administrator prior to issuance of floodplain development permit; or
 - (b) A Conditional Letter of Map Revision (CLOMR) has been approved by FEMA. A Letter of Map Revision (LOMR) must also be obtained within six months of completion of the proposed encroachment.
- (2) If Article 7.1.5, Section F (1) is satisfied, all development shall comply with all applicable flood hazard reduction provisions.
- (3) ~~No mobile homes shall be permitted, except replacement mobile homes in an existing mobile home park or subdivision, provided the following provisions are met:~~
Manufactured homes may be permitted provided the following provisions are met:
 - (a) The anchoring and the elevation standards of Article 7.1.5, Section B (3); and
 - (b) The encroachment standards of Article 7.1.5, Section F (1).

G. Coastal High Hazard Areas (Zone VE)

Coastal High Hazard Areas are Special Flood Hazard Areas established in Article 7.1.3, Section B, and designated as Zones VE. These areas have special flood hazards associated with high velocity waters from storm surges or seismic activity and, therefore, all new construction and substantial improvements shall meet the following provisions in addition to the provisions of Article 7.1.5, Sections A and B:

- (1) All new construction and substantial improvements shall:
 - (a) Be located landward of the reach of mean high tide;
 - (b) ~~Be located landward of the first line of stable natural vegetation; and~~
 - (b) Comply with all applicable CAMA setback requirements.
- (2) All new construction and substantial improvements shall be elevated so that the bottom of the lowest horizontal structural member of the lowest floor (excluding pilings or columns) is no lower than the regulatory flood protection elevation. Floodproofing shall not be utilized on any structures in Coastal High Hazard Areas to satisfy the regulatory flood protection elevation requirements.
- (3) All new construction and substantial improvements shall have the space below the bottom of the lowest horizontal structural member of the lowest floor free of obstruction so as not to impede the flow of flood waters, with the following exceptions:

- (a) Open wood or plastic latticework or insect screening may be permitted below the lowest floor for aesthetic purposes only and must be designed to wash away in the event of wave impact and in accordance with the provisions of Article 7.1.5, Section B(4)(e)(i). Design plans shall be submitted in accordance with the provisions of Article 4, Section B(1)(d)(iii)(2); or
 - (b) Breakaway walls may be permitted provided they meet the criteria set forth in Article 7.1.5, Section B(4)(a),(b),(c)&(e)(ii). Design plans shall be submitted in accordance with the provisions of Article 7.1.4, Section B(1)(d)(iii)(1).
- (4) All new construction and substantial improvements shall be securely anchored to pile or column foundations. All pilings and columns and the structure attached thereto shall be anchored to resist flotation, collapse, and lateral movement due to the effect of wind and water loads acting simultaneously on all building components.
- (a) Water loading values used shall be those associated with the base flood.
 - (b) Wind loading values used shall be those required by the current edition of the North Carolina State Building Code.
- (5) For concrete pads, including patios, decks, parking pads, walkways, driveways, pool decks, etc. the following is required:
- (a) Shall be structurally independent of the primary structural foundation system of the structure and shall not adversely affect structures through redirection of floodwaters or debris; and
 - (b) Shall be constructed to breakaway cleanly during design flood conditions, shall be frangible, and shall not produce debris capable of causing damage to any structure. (The installation of concrete in small segments (approximately 4 feet x 4 feet) that will easily break up during the base flood event, or score concrete in 4 feet x 4 feet maximum segments is acceptable to meet this standard); and
 - (c) Reinforcing, including welded wire fabric, shall not be used in order to minimize the potential for concreted pads being a source of debris; and
 - (d) Pad thickness shall not exceed 4 inches; or
 - (e) Provide a design professional's certification stating the design and method of construction to be used meet the applicable criteria of this section
- (6) For swimming pools and spas, the following is required:
- (a) Be designed to withstand all flood-related loads and load combinations.
 - (b) Be elevated so that the lowest horizontal structural member is elevated above the RFPE; or
 - (c) Be designed and constructed to break away during design flood conditions without producing debris capable of causing damage to any structure; or
 - (d) Be sited to remain in the ground during design flood conditions without obstructing flow that results in damage to any structure.

- (e) Registered design professionals must certify to local officials that a pool or spa beneath or near a VE Zone building will not be subject to flotation or displacement that will damage building foundations or elevated portions of the building or any nearby buildings during a coastal flood.
 - (f) Pool equipment shall be located above the RFPE whenever practicable. Pool equipment shall not be located beneath an elevated structure.
- (7) All elevators, vertical platform lifts, chair lifts, etc., the following is required:
- (a) Elevator enclosures must be designed to resist hydrodynamic and hydrostatic forces as well as erosion, scour, and waves.
 - (b) Utility equipment in Coastal High Hazard Areas (VE Zones) must not be mounted on, pass through, or be located along breakaway walls.
 - (c) The cab, machine/equipment room, hydraulic pump, hydraulic reservoir, counter weight and roller guides, hoist cable, limit switches, electric hoist motor, electrical junction box, circuit panel, and electrical control panel are all required to be above RFPE. When this equipment cannot be located above the RFPE, it must be constructed using flood damage-resistant components.
 - (d) Elevator shafts/enclosures that extend below the RFPE shall be constructed of reinforced masonry block or reinforced concrete walls and located on the landward side of the building to provide increased protection from flood damage. Drainage must be provided for the elevator pit.
 - (e) Flood damage-resistant materials can also be used inside and outside the elevator cab to reduce flood damage. Use only stainless-steel doors and door frames below the BFE. Grouting in of door frames and sills is recommended.
 - (f) If an elevator is designed to provide access to areas below the BFE, it shall be equipped with a float switch system that will activate during a flood and send the elevator cab to a floor above the RFPE.
 - (g) A registered professional engineer or architect shall certify that the design, specifications and plans for construction are in compliance with the provisions of Article 7.1.4, Section B and Article 7.1.5, Section G(3) and (4), on the current version of the North Carolina V-Zone Certification form or equivalent local version. In addition, prior to the Certificate of Compliance/Occupancy issuance, a registered professional engineer or architect shall certify the finished construction is compliant with the design, specifications and plans for VE Zone construction.
- (8) ~~Property owners shall be required to execute and record a non-conversion agreement prior to issuance of a building permit declaring that the area below the lowest floor, or the detached accessory building shall not be improved, or otherwise converted; Brunswick County will have the right to inspect the enclosed area. This agreement shall be recorded with the Brunswick County Register of Deeds and shall transfer with the property in perpetuity. (OPTIONAL)~~
- (9) ~~Release of restrictive covenant. If a property which is bound by a non-conversion agreement is modified to remove enclosed areas below BFE, then the owner may request release of restrictive covenant after staff inspection and submittal of confirming documentation. (OPTIONAL)~~

(10) ~~A registered professional engineer or architect shall certify that the design, specifications and plans for construction are in compliance with the provisions of Article 7.1.4, Section B and Article 7.1.5, Section G(3) and (4), on the current version of the North Carolina V-Zone Certification form or equivalent local version. In addition, prior to the Certificate of Compliance/Occupancy issuance, a registered professional engineer or architect shall certify the finished construction is compliant with the design, specifications and plans for VE Zone construction. (OPTIONAL)~~

(8) Fill/Grading

(a) Minor grading and the placement of minor quantities of nonstructural fill may be permitted for landscaping and for drainage purposes under and around buildings and for support of parking slabs, pool decks, patios and walkways.

(b) The fill material must be similar and consistent with the natural soils in the area.

(c) The placement of site-compatible, non-structural fill under or around an elevated building is limited to two (2) feet. Fill greater than two (2) feet must include an analysis prepared by a qualified registered design professional demonstrating no harmful diversion of floodwaters or wave runup and wave reflection that would increase damage to adjacent elevated buildings and structures.

(d) Nonstructural fill with finished slopes that are steeper than five (5) units horizontal to one (1) unit vertical shall be permitted only if an analysis prepared by a qualified registered design professional demonstrates no harmful diversion of floodwaters or wave runup and wave reflection that would increase damage to adjacent elevated buildings and structures.

(9) There shall be no alteration of sand dunes or mangrove stands which would increase potential flood damage.

(10) ~~No mobile homes shall be permitted except in an existing mobile home park or subdivision. A replacement mobile home may be placed on a lot in an existing mobile home park or subdivision provided the anchoring and elevation standards of this Section have been satisfied.~~

No manufactured homes shall be permitted except in an existing manufactured home park or subdivision. A replacement manufactured home may be placed on a lot in an existing manufactured home park or subdivision provided the anchoring and elevation standards of this Section have been satisfied.

(11) ~~Recreational vehicles may be permitted in Coastal High Hazard Areas provided that they meet the Recreational Vehicle criteria of Section 7.1.5.B.6.i and the Temporary Structure provisions of Section 7.1.5.B.7.~~

(11) Recreational vehicles may be permitted in Coastal High Hazard Areas provided that they meet the Recreational Vehicle criteria of Article 7.1.5, Section B(6)(a).

(12) A deck that is structurally attached to a building or structure shall have the bottom of the lowest horizontal structural member at or above the Regulatory Flood Protection Elevation and any supporting members that extend below the Regulatory Flood Protection Elevation shall comply with the foundation requirements that apply to the building or structure, which shall be designed to accommodate any increased loads resulting from the attached deck. The increased loads must be considered in the design of the primary structure and included in the V-Zone Certification required under Article 7.1.4, Section B, (3)(f).

(13) A deck or patio that is located below the Regulatory Flood Protection Elevation shall be structurally independent from buildings or structures and their foundation systems, and shall be designed and

constructed either to remain intact and in place during design flood conditions or to break apart into small pieces to minimize debris during flooding that is capable of causing structural damage to the building or structure or to adjacent buildings and structures.

(14) In coastal high hazard areas, development activities other than buildings and structures shall be permitted only if also authorized by the appropriate state or local authority; if located outside the footprint of, and not structurally attached to, buildings and structures; and if analyses prepared by qualified registered design professionals demonstrate no harmful diversion of floodwaters or wave runup and wave reflection that would increase damage to adjacent buildings and structures. Such other development activities include but are not limited to:

- (a) Bulkheads, seawalls, retaining walls, revetments, and similar erosion control structures;
- (b) Solid fences and privacy walls, and fences prone to trapping debris, unless designed and constructed to fail under flood conditions less than the design flood or otherwise function to avoid obstruction of floodwaters.

(15) No more than four (4) electrical outlets and no more than four (4) electrical switches may be permitted below RFPE unless required by building code.

H. Standards for Coastal A Zones (Zone CAZ) LiMWA (LIMIT OF MODERATE WAVE ACTION)

Structures in CAZs shall be designed and constructed to meet V Zone requirements, including requirements for breakaway walls. However, the NFIP regulations also require flood openings in walls surrounding enclosures below elevated buildings in CAZs (see Technical Bulletin 1, Openings in Foundation Walls and Walls of Enclosures). Breakaway walls used in CAZs must have flood openings that allow for the automatic entry and exit of floodwaters to minimize damage caused by hydrostatic loads. Openings also function during smaller storms or if anticipated wave loading does not occur with the base flood.

- (1) All new non-residential construction and substantial improvements shall be elevated so that the bottom of the lowest horizontal structural member of the lowest floor (excluding pilings or columns) is no lower than the regulatory flood protection elevation. Floodproofing shall not be utilized on any structures in Coastal A Zones to satisfy the regulatory flood protection elevation requirements.
- (2) All new non-residential construction and substantial improvements shall have the space below the lowest horizontal structural member free of obstruction so as not to impede the flow of flood waters, with the following exceptions:
 - i. Open wood latticework or insect screening may be permitted below the lowest floor for aesthetic purposes only and must be designed to wash away in the event of wave impact and in accordance with the provisions of Article 7.1.5, Section B(4)(e)(i). Design plans shall be submitted in accordance with the provisions of Article 7.1.4, Section B(1)(d)(iii)(2); or
 - ii. Breakaway walls may be permitted provided they meet the criteria set forth in Article 7.1.5, Section B(4)(e)(ii). Design plans shall be submitted in accordance with the provisions of Article 7.1.4, Section B(1)(d)(iii)(1).
- (3) All new construction and substantial improvements shall include, in Zones CAZ, flood openings to automatically equalize hydrostatic flood forces on walls by allowing for the entry and exit of floodwaters. To meet this requirement, the openings must either be certified by a professional engineer or architect or meet or exceed the design criteria in Article 7.1.5, Section B(4)(d).

- (4) Concrete pads, including patios, decks, parking pads, walkways, driveways, etc. must meet the provisions of Article 7.1.5, Section G(5).
- (5) All new non-residential construction and substantial improvements shall meet the provisions of Article 7.1.5, Section G(3)
- (6) A registered professional engineer or architect shall certify that the design, specifications and plans for construction are in compliance with the provisions of Article 7.1.4, Section B and Article 7.1.5, Section G(3) and (4), on the current version of the North Carolina V-Zone Certification form or a locally developed V-Zone Certification form.
- (7) Recreational vehicles may be permitted in Coastal A Zones provided that they meet the Recreational Vehicle criteria of Article 7.1.5, Section B(6)(a).
- (8) Fill/Grading must meet the provisions of Article 7.1.5, Section G(11)
- (9) Decks and patios must meet the provisions of Article 7.1.5 Section G(15) and (16).
- (10) In coastal high hazard areas, development activities other than buildings and structures must meet the provisions of Article 7.1.5, Section G(17)

~~I. Standards for Areas of Shallow Flooding (Zone AO) DELETED~~

7.1.6. LEGAL STATUS PROVISIONS

A. Effect on Rights and Liabilities Under the Existing Flood Damage Prevention Ordinance

~~This Section in part comes forward by re-enactment of some of the provisions of the flood damage prevention ordinance enacted April 1, 1985, as amended, and is not the intention to repeal but rather to reenact and continue to enforce without interruption of such existing provisions, so that all rights and liabilities that have accrued thereunder are reserved and may be enforced. The enactment of this Ordinance shall not affect any action, suit, or proceeding instituted or pending. All provisions of the flood damage prevention ordinance of Brunswick County enacted on April 1, 1985, as amended, which are not reenacted herein are repealed.~~

This ordinance in part comes forward by re-enactment of some of the provisions of the Flood Damage Prevention Ordinance enacted April 1st 1985 as amended, and it is not the intention to repeal but rather to re-enact and continue to enforce without interruption of such existing provisions, so that all rights and liabilities that have accrued thereunder are reserved and may be enforced. The enactment of this ordinance shall not affect any action, suit or proceeding instituted or pending. All provisions of the Flood Damage Prevention Ordinance of Brunswick County enacted on April 1st 1985, as amended, which are not reenacted herein are repealed.

The date of the initial Flood Damage Prevention Ordinance for each municipal jurisdiction within Brunswick County is as follows:

CID	Community Name	PRE/POST FIRM Date	First Ordinance Date
370442	BALD HEAD ISLAND, VILLAGE OF	4/15/1977	2/26/86
370545	BELVILLE, TOWN OF	6/2/2006	3/18/03

370453	BOILING SPRING LAKES, CITY OF	3/2/1989	2/6/89
370394	BOLIVIA, TOWN OF	6/2/2006	10/11/04
370295	BRUNSWICK COUNTY*	5/15/1986	04/01/85
370395	CALABASH, TOWN OF	2/4/1988	11/30/87
370517	CAROLINA SHORES, TOWN OF	1/26/1999	11/30/87
370391	CASWELL BEACH, TOWN OF	1/17/1986	05/06/76
375352	HOLDEN BEACH, TOWN OF	5/26/1972	11/14/76
370471	LELAND, TOWN OF	10/19/1992	9/17/1992
375354	LONG BEACH, TOWN OF	3/26/1971	3/26/71
370593	NAVASSA, TOWN OF	6/2/2006	5/30/06
370513	NORTHWEST, CITY OF	11/12/1998	11/12/98
370523	OAK ISLAND, TOWN OF	7/1/1999	07/01/99
375357	OCEAN ISLE BEACH, TOWN OF	11/17/72	11/17/72
370388	SHALLOTTE, TOWN OF	1/3/1986	1/20/88
370028	SOUTHPORT, CITY OF	4/15/1977	5/24/74
370530	ST JAMES, TOWN OF	6/27/2000	12/7/99
375359	SUNSET BEACH, TOWN OF	11/17/1972	11/18/72
370648	VARNAMTOWN, TOWN OF	5/30/2001	1/13/97
370030	YAUPON BEACH, TOWN OF	2/16/1977	2/16/1977

B. Effect Upon Outstanding Floodplain Development Permits

~~Nothing herein contained shall require any change in the plans, construction, size, or designated use of any development or any part thereof for which a floodplain development permit has been granted by the floodplain administrator or his or her authorized agents at the time of passage of this Section; provided, however that whenever construction is not begun under such outstanding permit within a period of six months subsequent to the date of issuance of the outstanding permit, construction or use shall be in conformance with the provisions of this Section.~~

Nothing herein contained shall require any change in the plans, construction, size, or designated use of any development or any part thereof for which a floodplain development permit has been granted by the Floodplain Administrator or his or her authorized agents before the time of passage of this ordinance; provided, however, that when construction is not begun under such outstanding permit within a period of six (6) months subsequent to the date of issuance of the outstanding permit, construction or use shall be in conformity with the provisions of this ordinance.

C. Severability

If any section, clause, sentence, or phrase of the Ordinance is held to be invalid or unconstitutional by any court of competent jurisdiction, then said holding shall in no way effect the validity of the remaining portions of this Ordinance.

D. Effective Date

This ordinance shall become effective August 28,2018.

E. Adoption Certification

I hereby certify that this is a true and correct copy of the Flood Damage Prevention Ordinance as adopted by the County Commissioners of Brunswick County, North Carolina, on the ____ day of _____, 2018.

WITNESS my hand and the official seal of _____, this the ____ day of _____,2018.

(signature)

CONSISTENCY STATEMENT

FOR BRUNSWICK COUNTY PLANNING BOARD

ZONING AMENDMENT DESCRIPTION: FLOOD DAMAGE PREVENTION ORDINANCE REVISIONS



THE BRUNSWICK COUNTY PLANNING BOARD RECOMMENDATION

THEREFORE, on the basis of all the foregoing, IT IS ORDERED that the ZONING AMENDMENT be recommended to the Board of Commissioners for

APPROVED – CONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment *is consistent with the CAMA Land Use Plan (Comprehensive Plan)* for the following reasons: _____

- The Planning Board further finds that the proposed zoning amendment *is reasonable and in the public interest* for the following reasons: _____

APPROVED – NOT CONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment *is NOT consistent* with the CAMA Land Use Plan (Comprehensive Plan) for the following reasons: _____

- The Planning Board further finds that the approval of the proposed zoning amendment will amend the CAMA Land Use Plan (Comprehensive Plan) and the following changes have been considered to meet the needs of the community: _____

- The Planning Board further finds that the proposed zoning amendment *is reasonable and in the public interest* for the following reasons: _____

DENIED – INCONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment **is** **is not** consistent with the CAMA Land Use Plan (Comprehensive Plan) and **is** **is not** in the public interest for the following reasons: _____

TABLED

- The Planning Board *TABLES* the proposed zoning amendment to **Next Planning Board Meeting** **A Future Planning Board Meeting** in _____ months.

Excerpt from N.C.G.S. § 153A-341:

Zoning regulations shall be designed to promote the public health, safety, and general welfare. To that end, the regulations may address, among other things, the following public purposes: to provide adequate light and air; to prevent the overcrowding of land; to avoid undue concentration of population; to lessen congestion in the streets; to secure safety from fire, panic, and dangers; and to facilitate the efficient and adequate provision of transportation, water, sewerage, schools, parks, and other public requirements. The regulations shall be made with reasonable consideration as to, among other things, the character of the district and its peculiar suitability for particular uses, and with a view to conserving the value of buildings and encouraging the most appropriate use of land throughout the county. In addition, the regulations shall be made with reasonable consideration to expansion and development of any cities within the county, so as to provide for their orderly growth and development.

BRUNSWICK COUNTY BUILDING INSPECTIONS

BRUNSWICK COUNTY GOVERNMENT CENTER
BUILDING I
75 COURTHOUSE DRIVE, N.E.
BOLIVIA, NORTH CAROLINA 28422

MAILING ADDRESS:

POST OFFICE BOX 249
BOLIVIA, NORTH CAROLINA 28422

TELEPHONE
(910) 253-2050
(800) 822-5986

FAX
(910) 253-2416

MEMORANDUM

June 11th, 2018

To: Planning Board

Subject: Proposed Flood Maps Approved by FEMA

The Federal Emergency Management Agency (FEMA) has released the proposed flood map changes related to Brunswick County. FEMA has recognized, through scientific studies and data analysis, a need to revise the current flood maps to protect lives and to minimize property damage during a flood event. Brunswick County must adopt the new flood maps in order to receive support from FEMA. The flood maps may be reviewed online at:

<http://fris.nc.gov/fris/Home.aspx?ST=NC>

or,

<https://flood.nc.gov/ncflood/>

CONSISTENCY STATEMENT

FOR BRUNSWICK COUNTY PLANNING BOARD

ZONING AMENDMENT DESCRIPTION: NEW FLOOD MAPS



THE BRUNSWICK COUNTY PLANNING BOARD RECOMMENDATION

THEREFORE, on the basis of all the foregoing, IT IS ORDERED that the ZONING AMENDMENT be recommended to the Board of Commissioners for

APPROVED – CONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment *is consistent with the CAMA Land Use Plan (Comprehensive Plan)* for the following reasons: _____

- The Planning Board further finds that the proposed zoning amendment *is reasonable and in the public interest* for the following reasons: _____

APPROVED – NOT CONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment *is NOT consistent with the CAMA Land Use Plan (Comprehensive Plan)* for the following reasons: _____

- The Planning Board further finds that the approval of the proposed zoning amendment will amend the CAMA Land Use Plan (Comprehensive Plan) and the following changes have been considered to meet the needs of the community: _____

- The Planning Board further finds that the proposed zoning amendment *is reasonable and in the public interest* for the following reasons: _____

DENIED – INCONSISTENT WITH COMPREHENSIVE PLAN

- The Planning Board finds that the proposed zoning amendment **is** **is not** consistent with the CAMA Land Use Plan (Comprehensive Plan) and **is** **is not** in the public interest for the following reasons: _____

TABLED

- The Planning Board **TABLES** the proposed zoning amendment to **Next Planning Board Meeting** **A Future Planning Board Meeting** in _____ months.

Excerpt from N.C.G.S. § 153A-341:

Zoning regulations shall be designed to promote the public health, safety, and general welfare. To that end, the regulations may address, among other things, the following public purposes: to provide adequate light and air; to prevent the overcrowding of land; to avoid undue concentration of population; to lessen congestion in the streets; to secure safety from fire, panic, and dangers; and to facilitate the efficient and adequate provision of transportation, water, sewerage, schools, parks, and other public requirements. The regulations shall be made with reasonable consideration as to, among other things, the character of the district and its peculiar suitability for particular uses, and with a view to conserving the value of buildings and encouraging the most appropriate use of land throughout the county. In addition, the regulations shall be made with reasonable consideration to expansion and development of any cities within the county, so as to provide for their orderly growth and development.